

Software Product Description

PRODUCT NAME: PDP-11 C for RSX-11M and
RSX-11M-PLUS, Version 1.2

SPD 09.30.03

DESCRIPTION

PDP-11 C for RSX-11M and RSX-11M-PLUS is a product of Mentec, Inc. and is licensed under Digital Equipment Corporation's Standard Terms and Conditions.

PDP-11 C for RSX-11M and RSX-11M-PLUS is a reliable language processor for Digital Equipment Corporation's proprietary operating systems on the PDP-11. PDP-11 C is highly compatible with the ANSI standard for the C language. PDP-11 C can be used to develop code for inclusion into resident libraries and other low level system routines.

PDP-11 C for RSX consists of a compiler, a Run-Time Library (RTL), and documentation.

The compiler produces machine code optimized for execution speed and memory efficiency. The compiler is highly compatible with the ANSI C standard, X3J11/90-013, February 14, 1990, and extends beyond ANSI requirements with several extensions for the PDP-11 family of central processors.

The compiler runs in native mode on the RSX-11M (mapped) and RSX-11M-PLUS host systems and produces PDP-11 object code compatible for all the supported target systems. These target systems are RSX-11M, RSX-11S, RSX-11M-PLUS, Micro/RSX, RSTS/E, RT-11, and VAX-11 RSX. The Run-Time Library is provided in object form.

The Run-Time Library provides run-time support that allows the user to perform many needed functions not provided from within the compiler itself. These features include:

- Native Standard I/O (STDIO) for each supported PDP-11 Operating System
- Arithmetic Operations
- Character Handling
- Localization
- Signal Handling
- Variable Arguments

- String Handling

Features

- Compatible with the ANSI C Standard (February 1990)
- Position Independent Code (PIC) Supervisor Mode Run-Time Library for the RSTS/E, RSX-11M-PLUS, and Micro/RSX target systems
- Function prototypes for declaring and checking function argument count and types
- Structured programming control flow constructs:
 - if...else construct for simple selection
 - switch statement for multi-choice selection with an arbitrary number of case statements
 - while, do, and for statements for iterative execution
- Flow modification statements:
 - break
 - continue
 - goto
- Data type for numeric, non-numeric, and systems programming:
 - Byte, word, and longword signed and unsigned integers
 - Integer constants in decimal, octal, and hexadecimal radices
 - Support for void data type
 - Single-character variables and constants
 - Single and double-precision numbers
 - Pointer variables containing the addresses of other variables
 - Data aggregates including array, structures, and unions
 - User-defined or enumerated (enum) data types with forward referencing allowed

- Storage allocation using:
 - Auto, static, register, and extern storage allocation classes for variables
 - Keywords (globalref, globaldef, and globalvalue) for sharing data among program modules
 - Psect Pragma for control of data attributes and data placement
- Concise arithmetic, relational, and logical operators
- Preprocessor control statements for:
 - File inclusion
 - Identifier substitution
 - Conditional compilation
 - Object module identification via pragmas
 - List File control via pragmas
 - Data storage control via pragmas
 - Source and list character sets via pragmas
- Support for DEC multi-national character sets
- Separate compilation capabilities
- Compiler generated listing file including optional:
 - Expanded preprocessor substitution listing
 - MACRO-11 file
- Generated Code
 - EIS or FPU
 - PIC or NONPIC
 - I/D Space supported or non I/D space
- Full support of RSX Executive Directives
- Support of RSX AST, RSX SST, and RSX CSM linkages to allow users to write:
 - Asynchronous system trap handlers
 - Synchronous system trap handlers
 - Supervisor mode library routines for RSX and RSTS/E systems

An Installation Verification Program (IVP) is provided to verify the installation of PDP-11 C and its RTL. The tests include compile-time error reporting (compiler test).

HARDWARE REQUIREMENTS

Any valid mapped RSX-11M or RSX-11M-PLUS system configuration with:

- Minimum of 64K bytes of user memory
For those systems that support separation of instruction and data (I/D) spaces, a minimum of 128K bytes or more of user memory is recommended for improved performance.
 - At least 3,500-4,000 blocks, 2,000 of which must be contiguous at compile-time
 - At least 5,500-8,000 blocks, 2,000 of which must be contiguous — required during installation procedure

These block counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration and software options selected.
- Extended Instruction Set (EIS)
- A device capable of reading one of the available distribution media.

OPTIONAL HARDWARE

Floating Point Processor as supported by the RSX-11M or RSX-11M-PLUS Operating System configuration.

HARDWARE NOT SUPPORTED

The Floating Instruction Set (FIS) is not supported. The processors affected by this are:

- LSI-11
- LSI-11/2
- LSI-11/03
- PDP-11/35
- PDP-11/40

SOFTWARE REQUIREMENTS

RSX-11M or RSX-11M-PLUS Operating System

RSX-11S, at a minimum of Version 4.6 (Run-Time operations only)

Refer to the RSX-11M and RSX-11M-PLUS Software Product Description (SPD 14.35.xx and SPD 14.70.xx) for the required versions.

OPTIONAL SOFTWARE

None

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

MEDIA DISTRIBUTION

The distribution Media Codes are described below. Specify the desired Media Code at the end of the Order Number, e.g., QJV69-H5 = binaries on TK50 Tape Cartridge.

5 = TK50 Tape Cartridge

M = 9-track 1600 BPI Magtape (PE)

Z = No hardware dependency

ORDERING INFORMATION

License Options:

For all Class L Systems¹

Single-Use License: QYV69-UZ

For all Class H Systems²

Single-Use License: QJV69-UZ

Media and Service Options:

Software Media/Documentation: QJV69-H*

Software Documentation: QJV66-GZ

Software Product Services: QJV69-**

* Denotes variant fields. For additional information on available licenses, services, and media, refer to the appropriate price book.

Note: The availability of these software product options and services may vary by country. Customers should contact their local Digital office for information on availability.

¹ Class L Systems(low-end systems):

- All Q-bus models and systems
- KD11, KDF11, KDJ11 CPU modules
- DCT11, DCF11, DCJ11 microprocessor chips

² Class H Systems(high-end systems):

- All UNIBUS models and system

SOFTWARE LICENSING

This software is furnished under the licensing provisions of Digital Equipment Corporation's Standard Terms and Conditions. For more information about Digital's licensing terms and policies, contact your local Digital office.

Note: The software being licensed is warranted only if the hardware configuration on which the software is to be run is a configuration explicitly supported by the RSX-11M (SPD 14.35.xx) or RSX-11M-PLUS (SPD 14.70.xx) Operating Systems.

SOFTWARE PRODUCT SERVICES

A variety of service options are available. For more information, please contact your local Digital office.

SOFTWARE WARRANTY

Warranty for this software product is provided by Digital with the purchase of a license for the product as defined in the Software Warranty Addendum of this SPD.

TM The DIGITAL Logo, DEC, KD11, Q-bus, PDP-11 C, Micro/RXS, RSTS/E, RSX, RSX-11M, RSX-11S, RSX-11M-PLUS, RT, RT-11, TK, UNIBUS, and VAX-11 RSX are trademarks of Digital Equipment Corporation.

