
OpenVMS/Hanyu RTL Chinese Processing (HSY\$) Manual

Order Number: AA-PXHEB-TE

August 2005

This manual documents the library routines contained in the HSY\$ facility of the OpenVMS/Hanyu Run-Time Library.

Revision/Update Information: This document supersedes the Introduction to the Multi-byte Processing Run Time Library HSYSHR manual, Version 6.0

Software Version: OpenVMS/Hanyu Alpha Version 8.2

**Hewlett-Packard Company
Palo Alto, California**

© Copyright 2005 Hewlett-Packard Development Company, L.P.

Confidential computer software. Valid license from HP required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel and Itanium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

Printed in Singapore

This document was prepared using DECdocument, Version 3.3-1b.

Contents

Preface	vii
----------------------	-----

1 INTRODUCTION

1.1	Organization of HSYSHR	1-1
1.2	Features of HSYSHR	1-6
1.3	Linking with HSYSHR	1-6

2 MULTI-BYTE CHARACTER CONCEPTS

2.1	What is Multi-byte Character?	2-1
2.2	Proper Character Boundary	2-1
2.3	Full Form and Half Form Character	2-1
2.4	Multi-byte Character Unsigned Longword Representation	2-2

HSY\$ Reference Section

HSY\$CH_MOVE	HSY/STRI-3
HSY\$DX_TRIM	HSY/STRI-4
HSY\$DX_TRUNC	HSY/STRI-6
HSY\$TRIM	HSY/STRI-8
HSY\$TRUNC	HSY/STRI-9
HSY\$CH_GCHAR	HSY/READ-10
HSY\$CH_GNEXT	HSY/READ-11
HSY\$CH_NEXTG	HSY/READ-12
HSY\$CH_PCHAR	HSY/READ-13
HSY\$CH_PNEXT	HSY/READ-15
HSY\$CH_RCHAR	HSY/READ-17
HSY\$CH_RNEXT	HSY/READ-18
HSY\$CH_RPREV	HSY/READ-19
HSY\$CH_WCHAR	HSY/READ-20
HSY\$CH_WNEXT	HSY/READ-21
HSY\$DX_RCHAR	HSY/READ-22
HSY\$DX_RNEXT	HSY/READ-23
HSY\$DX_WCHAR	HSY/READ-24
HSY\$DX_WNEXT	HSY/READ-25
HSY\$CH_CURR	HSY/POIN-26
HSY\$CH_NEXT	HSY/POIN-27
HSY\$CH_PREV	HSY/POIN-28
HSY\$DX_POS_CURR	HSY/POIN-29
HSY\$DX_POS_NEXT	HSY/POIN-30

HSY\$DX_POS_PREV	HSY/POIN-31
HSY\$DX_SKPC	HSY/POIN-32
HSY\$POS_CURR	HSY/POIN-33
HSY\$POS_NEXT	HSY/POIN-35
HSY\$POS_PREV	HSY/POIN-36
HSY\$SKPC	HSY/POIN-38
HSY\$COMPARE	HSY/COMP-39
HSY\$DX_STR_EQUAL	HSY/COMP-41
HSY\$STR_EQUAL	HSY/COMP-43
HSY\$DX_LOCC	HSY/SEAR-45
HSY\$DX_POSITION	HSY/SEAR-46
HSY\$DX_STR_SEARCH	HSY/SEAR-47
HSY\$DX_STR_START	HSY/SEAR-49
HSY\$LOCC	HSY/SEAR-51
HSY\$POSITION	HSY/SEAR-52
HSY\$STR_SEARCH	HSY/SEAR-54
HSY\$STR_START	HSY/SEAR-56
HSY\$CH_NBYTE	HSY/COUN-58
HSY\$CH_NCHAR	HSY/COUN-59
HSY\$CH_SIZE	HSY/COUN-60
HSY\$DX_NOF_BYTE	HSY/COUN-61
HSY\$DX_NOF_CHAR	HSY/COUN-62
HSY\$IS_ALPHA	HSY/CHAR-63
HSY\$IS_DESCRIPTION	HSY/CHAR-64
HSY\$IS_DIGIT	HSY/CHAR-65
HSY\$IS_GENERAL	HSY/CHAR-66
HSY\$IS_GREEK	HSY/CHAR-67
HSY\$IS_IDEOGRAPH	HSY/CHAR-68
HSY\$IS_LEFT_PARENTHESIS	HSY/CHAR-69
HSY\$IS_LINE_DRAWING	HSY/CHAR-70
HSY\$IS_LOWER	HSY/CHAR-71
HSY\$IS_NO_FIRST	HSY/CHAR-72
HSY\$IS_NO_LAST	HSY/CHAR-73
HSY\$IS_PARENTHESIS	HSY/CHAR-74
HSY\$IS_RIGHT_PARENTHESIS	HSY/CHAR-75
HSY\$IS_ROMAN	HSY/CHAR-76
HSY\$IS_TECHNICAL	HSY/CHAR-77
HSY\$IS_UNIT	HSY/CHAR-78
HSY\$IS_UPPER	HSY/CHAR-79
HSY\$IS_VALID	HSY/CHAR-80
HSY\$DX_DATE_TIME	HSY/DATE-81
HSY\$DX_TIME	HSY/DATE-83
HSY\$CHG_GENERAL	HSY/CONV-84
HSY\$CHG_KEISEN	HSY/CONV-85
HSY\$CHG_ROM_CASE	HSY/CONV-86
HSY\$CHG_ROM_FULL	HSY/CONV-87
HSY\$CHG_ROM_HALF	HSY/CONV-88

HSY\$CHG_ROM_LOWER	HSY/CONV-89
HSY\$CHG_ROM_SIZE	HSY/CONV-90
HSY\$CHG_ROM_UPPER	HSY/CONV-91
HSY\$DX_TRA_ROM_CASE	HSY/CONV-92
HSY\$DX_TRA_ROM_FULL	HSY/CONV-94
HSY\$DX_TRA_ROM_HALF	HSY/CONV-96
HSY\$DX_TRA_ROM_LOWER	HSY/CONV-98
HSY\$DX_TRA_ROM_SIZE	HSY/CONV-100
HSY\$DX_TRA_ROM_UPPER	HSY/CONV-102
HSY\$DX_TRA_SYMBOL	HSY/CONV-104
HSY\$TRA_ROM_CASE	HSY/CONV-106
HSY\$TRA_ROM_FULL	HSY/CONV-108
HSY\$TRA_ROM_HALF	HSY/CONV-110
HSY\$TRA_ROM_LOWER	HSY/CONV-112
HSY\$TRA_ROM_SIZE	HSY/CONV-114
HSY\$TRA_ROM_UPPER	HSY/CONV-116
HSY\$TRA_SYMBOL	HSY/CONV-118

Tables

1-1	HSYSHR routine groups	1-1
1-2	String Routines	1-2
1-3	Read Write Routines	1-2
1-4	Pointer Routines	1-2
1-5	Comparison Routines	1-3
1-6	Searching Routines	1-3
1-7	Counting Routines	1-4
1-8	Character Type Routines	1-4
1-9	Date Time Routines	1-5
1-10	Conversion Routines	1-5

Preface

This manual provides users of the OpenVMS/Hanyu operating system with detailed usage and reference information on library routines supplied in the HSY\$ facility of the OpenVMS/Hanyu Run-Time Library for Chinese processing.

Intended Audience

This manual is intended for application programmers who want to write applications for Chinese processing.

Document Structure

This manual is organized into two parts as follows:

- The introductory chapters provide reference material on specific types of HSY\$ library routines and Chinese processing concepts.
Chapter 1 provides a brief overview of the HSY\$ facility and lists the HSY\$ routines and their functions.
Chapter 2 provides an overview of the concept of Chinese characters and their representation in the OpenVMS/Hanyu operating system.
- The HSY\$ Reference Section describes each library routine contained in the HSY\$ Run-Time Library facility in OpenVMS/Hanyu. This information is presented using the documentation format described in *OpenVMS Programming Interfaces: Calling a System Routine*.

Associated Document

A description of how the Run-Time Library routines are accessed is presented in *OpenVMS Programming Interface: Calling a System Routine*. The HSY\$ Run-Time Library routines can be used with other RTL facilities provided in OpenVMS and OpenVMS/Hanyu. Descriptions of the other RTL facilities and their corresponding routines are presented in the following books:

- *OpenVMS/Hanyu RTL Chinese Screen Management (SMG\$) Manual*
- *OpenVMS RTL Library (RTL\$) Manual*
- *OpenVMS VAX RTL Mathematics (MTH\$) Manual*
- *OpenVMS RTL General Purpose (OTS\$) Manual*
- *OpenVMS RTL String Manipulation (STR\$) Manual*

Application programmers using any programming language can refer to *Guide to Creating OpenVMS Modular Procedures* for writing modular and reentrant code, and *OpenVMS/Hanyu User Guide* for understanding the DEC Hanyu character set.

High-level language programmers will find additional information on calling Run-Time Library routines in their language reference manuals. Additional information may also be found in the programming language user's guide provided with your OpenVMS programming language software.

For a complete list and description of the manuals in the OpenVMS documentation set, see *Overview of OpenVMS Documentation*.

For additional information about HP OpenVMS products and services, visit the following World Wide Web address:

<http://www.hp.com/go/openvms>

Conventions

The following conventions may be used in this manual:

Ctrl/ <i>x</i>	A sequence such as Ctrl/ <i>x</i> indicates that you must hold down the key labeled Ctrl while you press another key or a pointing device button.
PF1 <i>x</i>	A sequence such as PF1 <i>x</i> indicates that you must first press and release the key labeled PF1 and then press and release another key or a pointing device button.
Return	In examples, a key name enclosed in a box indicates that you press a key on the keyboard. (In text, a key name is not enclosed in a box.) In the HTML version of this document, this convention appears as brackets, rather than a box.
...	A horizontal ellipsis in examples indicates one of the following possibilities: <ul style="list-style-type: none">• Additional optional arguments in a statement have been omitted.• The preceding item or items can be repeated one or more times.• Additional parameters, values, or other information can be entered.
.	A vertical ellipsis indicates the omission of items from a code example or command format; the items are omitted because they are not important to the topic being discussed.
()	In command format descriptions, parentheses indicate that you must enclose choices in parentheses if you specify more than one.
[]	In command format descriptions, brackets indicate optional choices. You can choose one or more items or no items. Do not type the brackets on the command line. However, you must include the brackets in the syntax for OpenVMS directory specifications and for a substring specification in an assignment statement.

	In command format descriptions, vertical bars separate choices within brackets or braces. Within brackets, the choices are optional; within braces, at least one choice is required. Do not type the vertical bars on the command line.
{ }	In command format descriptions, braces indicate required choices; you must choose at least one of the items listed. Do not type the braces on the command line.
bold type	Bold type represents the introduction of a new term. It also represents the name of an argument, an attribute, or a reason.
<i>italic type</i>	Italic type indicates important information, complete titles of manuals, or variables. Variables include information that varies in system output (Internal error <i>number</i>), in command lines (<i>/PRODUCER=name</i>), and in command parameters in text (where <i>dd</i> represents the predefined code for the device type).
Example	This typeface indicates code examples, command examples, and interactive screen displays. In text, this type also identifies URLs, UNIX commands and pathnames, PC-based commands and folders, and certain elements of the C programming language.
UPPERCASE TYPE	Uppercase type indicates a command, the name of a routine, the name of a file, or the abbreviation for a system privilege.
-	A hyphen at the end of a command format description, command line, or code line indicates that the command or statement continues on the following line.
numbers	All numbers in text are assumed to be decimal unless otherwise noted. Nondecimal radices—binary, octal, or hexadecimal—are explicitly indicated.

INTRODUCTION

The OpenVMS/Hanyu Chinese Processing Run-Time Library (or simply HSYSHR) is a library of prewritten, commonly-used routines that perform a wide variety of multi-byte Chinese language processing operations. It represents the HSY\$ facility of the OpenVMS/Hanyu Run-Time Library. All HSY\$ routines follow the OpenVMS Procedure Calling Standard. They are callable from any programming languages supported in OpenVMS/Hanyu, thus increasing program flexibility.

1.1 Organization of HSYSHR

Routines in HSYSHR are grouped according to the types of tasks they perform. Altogether, there are nine groups of routines. All routine names are prefixed by the facility code HSY\$. Those routines prefixed by HSY\$DX_ pass string by descriptor, otherwise strings are passed by the address of the starting position of the string. Table 1–1 shows the nine groups of HSY\$ routines.

Table 1–1 HSYSHR routine groups

Group	Types of Tasks Performed
String Routines	Perform manipulation of strings containing multi-byte or mixed ASCII and multi-byte characters.
Read Write Routines	Perform read and write of ASCII and multi-byte characters in user buffers.
Pointer Routines	Perform character pointer manipulation.
Comparison Routines	Perform comparison of strings containing multi-byte or mixed ASCII multi-byte characters.
Searching Routines	Perform searching of substrings in buffer containing multi-byte or mixed ASCII and multi-byte characters.
Counting Routines	Perform counting of bytes and characters in buffer containing multi-byte or mixed ASCII and multi-byte characters.
Character Type Routines	Perform checking of different classes of local language symbols and characters.
Date Time Routines	Provide local language date time format.
Conversion Routines	Perform various multi-byte character specific conversion.

The following tables list all routines available for each of the aforementioned groups, followed by brief statements of the routines' functions.

INTRODUCTION

1.1 Organization of HSYSHR

Table 1–2 String Routines

Routine Name	Function
HSY\$CH_MOVE	Moves a substring from a specified source buffer to a specified destination buffer.
HSY\$TRIM	Trims trailing one-byte and multi-byte spaces and TAB characters.
HSY\$TRUNC	Returns the position of the first character that follows the truncated string.
HSY\$DX_TRIM	Trims trailing one-byte and multi-byte spaces and TAB characters.
HSY\$DX_TRUNC	Truncates the input string to the specified length.

Table 1–3 Read Write Routines

Routine Name	Function
HSY\$CH_GCHAR	Reads the current character.
HSY\$CH_GNEXT	Reads the current character.
HSY\$CH_NEXTG	Reads the next character, skipping the current character.
HSY\$CH_RCHAR	Reads the current character.
HSY\$CH_RNEXT	Reads the current character.
HSY\$CH_RPREV	Reads the previous character.
HSY\$DX_RCHAR	Reads the current character.
HSY\$DX_RNEXT	Reads the current character.
HSY\$CH_PCHAR	Writes a specified character to the current position of a buffer.
HSY\$CH_PNEXT	Writes a specified character to the current position of a buffer.
HSY\$CH_WCHAR	Writes a specified character to the current position of a buffer.
HSY\$CH_WNEXT	Writes a specified character to the current position of a buffer.
HSY\$DX_WCHAR	Writes a specified character.
HSY\$DX_WNEXT	Writes a specified character.

Table 1–4 Pointer Routines

Routine Name	Function
HSY\$SKPC	Skips a specified character.
HSY\$CH_CURR	Points to the first byte of the current character.
HSY\$CH_NEXT	Points to the first byte of the next character.

(continued on next page)

Table 1–4 (Cont.) Pointer Routines

Routine Name	Function
HSY\$CH_PREV	Points to the first byte of the previous character.
HSY\$POS_CURR	Points to the first byte of the current character.
HSY\$POS_NEXT	Points to the first byte of the next character.
HSY\$POS_PREV	Points to the first byte of the previous character.
HSY\$DX_SKPC	Skips a specified character.
HSY\$DX_POS_CURR	Points to the first byte of the current character.
HSY\$DX_POS_NEXT	Points to the first byte of the next character.
HSY\$DX_POS_PREV	Points to the first byte of the previous character.

Table 1–5 Comparison Routines

Routine Name	Function
HSY\$COMPARE	Compares two specified strings.
HSY\$STR_EQUAL	Checks if two specified character strings are equal.
HSY\$DX_STR_EQUAL	Checks if two specified character strings are equal.

Table 1–6 Searching Routines

Routine Name	Function
HSY\$LOCC	Locates the position of the first occurrence of the specified character.
HSY\$POSITION	Searches the first occurrence of a specified substring in the input string.
HSY\$STR_SEARCH	Searches the first occurrence of a specified substring in the input string with conversion performed prior to comparing the characters.
HSY\$STR_START	Checks if the specified substring is found in another input string and starts from the first byte of the input string.
HSY\$DX_LOCC	Locates the position of the first occurrence of the specified character.
HSY\$DX_POSITION	Searches the first occurrence of a substring in a specified string.
HSY\$DX_STR_SEARCH	Searches the first occurrence of a specified substring in the input string.
HSY\$DX_STR_START	Checks if the specified substring is found in another input string and starts from the first byte of the input string.

INTRODUCTION

1.1 Organization of HSYSHR

Table 1–7 Counting Routines

Routine Name	Function
HSY\$CH_SIZE	Tells the byte length of the specified character.
HSY\$CH_NCHAR	Returns the number of characters in a specified string.
HSY\$CH_NBYTE	Counts the number of bytes of a character string.
HSY\$DX_NOF_CHAR	Returns the number of characters in a specified number of bytes.
HSY\$DX_NOF_BYTE	Counts the number of bytes of a character string.

Table 1–8 Character Type Routines

Routine Name	Function
HSY\$IS_VALID	Checks if the input character is a valid multi-byte character.
HSY\$IS_IDEOGRAPH	Checks if the input multi-byte character is an ideographic multi-byte character.
HSY\$IS_DESCRIPTION	Checks if the input character is a multi-byte local language punctuation.
HSY\$IS_TECHNICAL	Checks if the input character is a scientific or mathematical multi-byte symbol character.
HSY\$IS_UNIT	Checks if the input character is a multi-byte standard unit symbol character.
HSY\$IS_GENERAL	Checks if the input character is a multi-byte general symbol character.
HSY\$IS_LINE_DRAWING	Checks if the input character is a multi-byte line drawing symbol character.
HSY\$IS_DIGIT	Checks if the input character is a one-byte or multi-byte numeric digit.
HSY\$IS_ROMAN	Checks if the input character is a one-byte or multi-byte English letter.
HSY\$IS_GREEK	Checks if the input character is a multi-byte Greek letter.
HSY\$IS_ALPHA	Checks if the input character is a Greek or Roman letter.
HSY\$IS_UPPER	Checks if the input character is an upper case Greek or Roman letter.
HSY\$IS_LOWER	Checks if the input character is a lower case Greek or Roman letter.
HSY\$IS_PARENTHESIS	Checks if the input character is a multi-byte parenthesis symbol character.
HSY\$IS_LEFT_PARENTHESIS	Checks if the input character is a multi-byte left parenthesis symbol character.
HSY\$IS_RIGHT_PARENTHESIS	Checks if the input character is a multi-byte right parenthesis symbol character.

(continued on next page)

Table 1–8 (Cont.) Character Type Routines

Routine Name	Function
HSY\$IS_NO_FIRST	Checks if the input character is a multi-byte "NO FIRST" character.
HSY\$IS_NO_LAST	Checks if the input character is a multi-byte "NO-LAST" character.

Table 1–9 Date Time Routines

Routine Name	Function
HSY\$DX_DATE_TIME	Returns the date and time in local language format.
HSY\$DX_TIME	Returns the date and time of the system time in local language format.

Table 1–10 Conversion Routines

Routine Name	Function
HSY\$CHG_KEISEN	Converts '0' to '9' and '.' to multi-byte line drawing characters.
HSY\$CHG_GENERAL	Performs general multi-byte conversion.
HSY\$CHG_ROM_FULL	Converts half form ASCII to full form ASCII.
HSY\$CHG_ROM_HALF	Converts full form ASCII to half form ASCII equivalence.
HSY\$CHG_ROM_SIZE	Toggles the form (full form or half form) of the input character.
HSY\$CHG_ROM_UPPER	Converts one-byte and multi-byte letters to upper case.
HSY\$CHG_ROM_LOWER	Converts one byte and multi-byte letters to lower case.
HSY\$CHG_ROM_CASE	Toggles the casing of one-byte and multi-byte letters of the input character.
HSY\$TRA_ROM_FULL	Converts half form ASCII to full form ASCII.
HSY\$TRA_ROM_HALF	Converts full form ASCII to half form ASCII equivalence.
HSY\$TRA_ROM_SIZE	Toggles the form (full form or half form) of the input string.
HSY\$TRA_ROM_UPPER	Converts one-byte and multi-byte letters to upper case.
HSY\$TRA_ROM_LOWER	Converts one-byte and multi-byte letters to lower case.
HSY\$TRA_ROM_CASE	Toggles the casing of one-byte and multi-byte letters found in the string.
HSY\$TRA_SYMBOL	Converts the sequence of a one-byte character to a string of multi-byte symbols.
HSY\$DX_TRA_ROM_FULL	Converts half form ASCII to full form ASCII.

(continued on next page)

INTRODUCTION

1.1 Organization of HSYSHR

Table 1–10 (Cont.) Conversion Routines

Routine Name	Function
HSY\$DX_TRA_ROM_HALF	Converts full form ASCII to half form ASCII equivalence.
HSY\$DX_TRA_ROM_SIZE	Toggles the form (full form or half form) of the input string.
HSY\$DX_TRA_ROM_UPPER	Converts one-byte and multi-byte letters to upper case.
HSY\$DX_TRA_ROM_LOWER	Converts one-byte and multi-byte letters to lower case.
HSY\$DX_TRA_ROM_CASE	Toggles the casing of one-byte and multi-byte letters found in the input string.
HSY\$DX_TRA_SYMBOL	Converts the sequence of a one-byte character to a string of multi-byte symbols.

1.2 Features of HSYSHR

HSYSHR provides the following features and capabilities:

- HSYSHR performs a wide range of general multi-byte processing operations. You can call the HSY\$ routines instead of writing your own code to perform the operation.
- Routines in HSYSHR follow the OpenVMS Procedure Calling Standard. It allows you to call any HSY\$ routines from any programming language supported in OpenVMS/Hanyu, thus increasing program flexibility.
- Because all routines are shared, they take up less virtual address space of a process.
- When new versions of the HSYSHR are installed, you do not need to revise your calling program, and generally do not need to relink.

1.3 Linking with HSYSHR

Routines in the HSYSHR execute entirely in the mode of the caller and are intended to be called in the user mode. To link your application that contains explicit calls to HSYSHR, use the following link command:

```
$ LINK program, SYS$LIBRARY:HSYIMGLIB.OLB/LIBRARY
```

MULTI-BYTE CHARACTER CONCEPTS

This chapter describes some important concepts of multi-byte character that are used throughout the documentation.

2.1 What is Multi-byte Character?

DEC Hanyu character set is implemented as a multi-byte character set containing Chinese characters, punctuation marks and various kinds of symbols. Each multi-byte character can either be a two-byte character or four-byte character. In OpenVMS/Hanyu, the DEC Hanyu character set is adopted, and Chinese characters are represented as multi-byte characters from the character set. For detailed discussion of the DEC Hanyu character set, please refer to *OpenVMS/Hanyu User Guide*.

2.2 Proper Character Boundary

In HSYSHR, most of the routines use characters as a processing entity contrary to conventional byte by byte processing. Some routines require the input character pointer pointing at the proper character boundary in the user buffer. "Pointing at the proper character boundary" means the character pointer should not point to the non-first-byte position of a multi-byte character.

2.3 Full Form and Half Form Character

In DEC Hanyu character set, there is a set of two-byte ASCII characters. To distinguish them from the conventional one-byte 7-bit ASCII characters, the terms "full form" and "half form" characters are used. Full form characters refer to two-byte ASCII characters whereas half form characters refer to one-byte 7-bit ASCII characters. Conversion services between full form and half form characters are provided by the conversion routines in HSYSHR. In some applications where character matching requires treating the full form and half form characters equivalent, the user can call the searching routines in HSYSHR and specify the conversion flag argument. Note that uppercasing and lowercasing can both be applied to these full form characters.

MULTI-BYTE CHARACTER CONCEPTS

2.4 Multi-byte Character Unsigned Longword Representation

2.4 Multi-byte Character Unsigned Longword Representation

In HSYSHR, multi-byte character representation in single character argument is different from that found in the character string argument. Single character argument uses unsigned longword integer representation whereas characters in the string argument use the normal character string representation. The following are two examples.

- The two-byte character B0A1(hex) is represented as follows:
Single character argument: (VMS Usage - longword_unsigned)

```
+---+---+---+---+
|00|00|B0|A1|
+---+---+---+---+
H                               L
```

In a string argument: (VMS Usage - char_string)

```
-----+---+   +---+
.... |A1|B0|....| | start of string
-----+---+   +---+
H                               L
```

- The four byte character C2CBB0A2(hex) is represented as follows:
Single character argument: (VMS Usage - longword_unsigned)

```
+---+---+---+---+
|C2|CB|B0|A2|
+---+---+---+---+
H                               L
```

In a string argument: (VMS Usage - char_string)

```
-----+---+---+   +---+
.... |A2|B0|CB|C2|....| | start of string
-----+---+---+   +---+
H                               L
```

The read routines in HSYSHR read the buffer with character string format and return the character read in unsigned longword format. The write routines write the character in unsigned longword format to the buffer. The character written will be in character string format.

HSY\$ Reference Section

This section provides detailed discussions of the routines provided in the Chinese Processing Run Time Library HSYSHR.

HSY\$CH_MOVE

HSY\$CH_MOVE moves a substring from a specified source buffer to a specified destination buffer.

Format

HSY\$CH_MOVE len,src,dst

Arguments

len

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the substring to be moved.

src

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the source buffer.

dst

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the destination buffer.

Description

This routine is multi-byte insensitive. If **len** is not specifying the proper multi-byte character boundary, e.g. it indicates the second byte of a two-byte character, then only half of the multi-byte character is moved to the last character of the destination string.

HSY\$DX_TRIM

HSY\$DX_TRIM

HSY\$DX_TRIM trims trailing one-byte and multi-byte spaces and TAB characters.

Format

HSY\$DX_TRIM dst,src,[len]

Returns

VMS Usage: cond_value
type: longword (unsigned)
access: write only
mechanism: by value

Arguments

dst

VMS Usage: char_string
type: character string
access: write only
mechanism: by descriptor

The destination string to store the trimmed string.

src

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

The source string that is to be converted.

len

VMS Usage: word_signed
type: word integer (signed)
access: write only
mechanism: by reference

The length in bytes of the trimmed string. If this optional argument is not supplied, no length information of the trimmed string will be returned to the caller.

Description

dst and **src** can contain one-byte and multi-byte characters.

CONDITION VALUES RETURNED

LIB\$_INVSTRDES	Invalid string descriptor. A string descriptor has an invalid value in its DSC\$B_CLASS field.
LIB\$_STRTRU	Procedure successfully completed. String truncated.

LIB\$_FATERRLIB

Fatal internal error. An internal consistency check has failed.

LIB\$_INSVIRMEM

Insufficient virtual memory.

SS\$_NORMAL

Procedure successfully completed.

HSY\$DX_TRUNC

HSY\$DX_TRUNC

HSY\$DX_TRUNC truncates the input string to the specified length.

Format

HSY\$DX_TRUNC dst,src,offset,[len]

Returns

VMS Usage: cond_value
type: longword (unsigned)
access: write only
mechanism: by value

Arguments

dst

VMS Usage: char_string
type: character string
access: write only
mechanism: by descriptor

The specified destination string to store the truncated string.

src

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

The specified source string to be truncated.

offset

VMS Usage: word_signed
type: word integer (signed)
access: read only
mechanism: by reference

The offset in bytes from the starting position of the source string which indicates the position of the first character just after the truncated string. Note that this offset may not be on the proper character boundary, e.g. it may point to the second byte of a two-byte character.

len

VMS Usage: word_signed
type: word integer (signed)
access: write only
mechanism: by reference

The length in bytes of the truncated string. If this optional argument is not supplied, no length information of the truncated string will be returned to the caller.

Description

The value returned in **len** may not necessarily be equal to the value specified in **offset** since **offset** may not be pointing at the first byte of a multi-byte character. In any case, the character indicated by **offset** will be treated as the first character that follows the truncated string.

CONDITION VALUES RETURNED

LIB\$_INVSTRDES	Invalid string descriptor. A string descriptor has an invalid value in its DSC\$_CLASS field.
LIB\$_STRTRU	Procedure successfully completed. Truncated string is further truncated due to insufficient space allocated in the destination string buffer.
LIB\$_FATERRLIB	Fatal internal error. An internal consistency check has failed.
LIB\$_INSVIRMEM	Insufficient virtual memory.
SS\$_NORMAL	Procedure successfully completed.

HSY\$TRIM

HSY\$TRIM

HSY\$TRIM trims trailing one-byte and multi-byte spaces and TAB characters.

Format

HSY\$TRIM str,len

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The offset in bytes from the starting position of the input string which indicates the position of the terminating character of the trimmed string. If the terminating character is a multi-byte character, the returned offset will be pointing to the first byte of the multi-byte character.

Arguments

str

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the input string to be trimmed.

len

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the input string.

Description

str can contain one-byte and multi-byte characters.

HSY\$TRUNC

HSY\$TRUNC returns the position of the first character that follows the truncated string.

Format

HSY\$TRUNC str,len,offset

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The offset in bytes which indicates the position of the first character just follows the truncated string. If this character is a multi-byte character, the offset will be pointing at the first byte of the multi-byte character.

Arguments

str

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the input string.

len

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the input string.

offset

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The offset in bytes of the character just follows the truncated string. It may not be on the proper character boundary, e.g. it can point to the second byte of a two-byte character.

Description

str can contain one-byte and multi-byte characters. This routine helps you to position **offset** to the proper character boundary. Its function is similar to routine **HSY\$CH_CURR** but with different parameter interface.

HSY\$CH_GCHAR

HSY\$CH_GCHAR

HSY\$CH_GCHAR reads the current character.

Format

HSY\$CH_GCHAR cur,end

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The current character.

Arguments

cur

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the current position of the specified current character. Note that this address must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

end

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the string terminating position plus one as illustrated below:

```
.. +---+---+---+---+
   |   |   |   |   |
   +---+---+---+---+
string                                     ^
                                         end
```

Description

This routine reads a character with end of buffer checking. FFFF (hex) will be returned when read past the end of buffer. If the current character is a one-byte 7-bit control character or one-byte 8-bit character (e.g. an 8-bit character followed by a 7-bit control character), the one-byte 7-bit or 8-bit character will be returned. No updating of current pointer is done since **cur** is passed by value.

HSY\$CH_GNEXT

HSY\$CH_GNEXT reads the current character.

Format

HSY\$CH_GNEXT cur,end

Returns

VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: write only
 mechanism: by value

The current character.

Arguments

cur

VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: modify
 mechanism: by reference

The address of the current position of the specified current character. Note that this address must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

end

VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: read only
 mechanism: by value

The address of the string terminating position plus one as illustrated below:

```

.. +---+---+---+---+
   |   |   |   |   |
   +---+---+---+---+
string                                ^
                                     end

```

Description

This routine reads a character with end of buffer checking. FFFF (hex) will be returned when read past the end of buffer. If the current character is a one-byte 7-bit control character or one-byte 8-bit character (e.g. an 8-bit character followed by a 7-bit control character), the one-byte 7-bit or 8-bit character will be returned. Updating of the current pointer is done. After the read action, **cur** will be updated to the next character position pointing at the proper character boundary. This routine is useful for successive character reading.

HSY\$CH_NEXTG

HSY\$CH_NEXTG

HSY\$CH_NEXTG reads the next character, skipping the current character.

Format

HSY\$CH_NEXTG cur,end

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The next character.

Arguments

cur

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: modify
mechanism: by reference

The address of the current position of the specified current character. Note that this address must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

end

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the string terminating position plus one as illustrated below:

```
.. +---+---+---+---+
   |   |   |   |   |
   +---+---+---+---+
string                                ^
                                     end
```

Description

This routine reads the next character, skipping the current character. FFFF (hex) will be returned when read past the end of buffer. If the next character is a one-byte 7-bit control character or one-byte 8-bit character (e.g. an 8-bit character followed by a 7-bit control character), the one-byte 7-bit or 8-bit character will be returned. Updating of the current pointer is done. After the read action, **cur** will be updated to the next character position pointing at the proper character boundary.

HSY\$CH_PCHAR

HSY\$CH_PCHAR writes a specified character to the current position of a buffer.

Format

HSY\$CH_PCHAR chr,cur,end

Returns

VMS Usage: longword_signed
 type: longword integer (signed)
 access: write only
 mechanism: by value

Either 1 or 0 is returned as status.

- 1 - Input character is successfully written to the specified position of the string.
- 0 - Input character is not written to the specified position of the string.

Arguments

chr

VMS Usage: longword_signed
 type: longword integer (signed)
 access: read only
 mechanism: by value

The character to be written to the specified current position of the string.

cur


VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: read only
 mechanism: by value

The address of the current position of the string where the input character is to be written to.

end

VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: read only
 mechanism: by value

The address of the string terminating position plus one as illustrated below:



HSY\$CH_PCHAR

Description

This routine writes a character to a specified position. End of buffer checking is performed to make sure there is enough space in the buffer for the character to be written since **chr** can be a multi-byte character.

HSY\$CH_PNEXT

HSY\$CH_PNEXT writes a specified character to the current position of a buffer.

Format

HSY\$CH_PNEXT chr,cur,end

Returns

VMS Usage: longword_signed
 type: longword integer (signed)
 access: write only
 mechanism: by value

Either 1 or 0 is returned as status.

- 1 - Input character is successfully written to the specified position of the string.
- 0 - Input character is not written to the specified position of the string.

Arguments

chr

VMS Usage: longword_signed
 type: longword integer (signed)
 access: read only
 mechanism: by value

The character to be written to the specified current position of the string. Note that the input character can either be one- or two-byte character.

cur

VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: modify
 mechanism: by reference

The address of the current position of the string where the input character is to be written to.

end

VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: read only
 mechanism: by value

The address of the string terminating position plus one as illustrated below:

```

  +---+---+---+---+
  .. |   |   |   |   |
  +---+---+---+---+
  string                                ^
                                         end

```

HSY\$CH_PNEXT

Description

This routine writes a character to a specified position. End of buffer checking is performed to make sure there is enough space in the buffer for the character to be written since **chr** can be a multi-byte character. Note that **cur** is updated. It points to the next character position after the write action. This routine is useful for successive writing of character to a buffer.

HSY\$CH_RCHAR

HSY\$CH_RCHAR reads the current character.

Format

HSY\$CH_RCHAR cur

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The current character.

Arguments

cur
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the current position of the specified current character. Note that this address must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

Description

This routine reads the current character. If the current character is a one-byte 7-bit control character or one-byte 8-bit character (e.g. an 8-bit character followed by a 7-bit control character), the one-byte 7-bit or 8-bit character will be returned.

HSY\$CH_RNEXT

HSY\$CH_RNEXT

HSY\$CH_RNEXT reads the current character.

Format

HSY\$CH_RNEXT cur

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The current character.

Arguments

cur
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: modify
mechanism: by reference

The address of the current position of the specified current character. Note that this address must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

Description

This routine reads the current character. If the current character is a one-byte 7-bit control character or one-byte 8-bit character (e.g. an 8-bit character followed by a 7-bit control character), the one-byte 7-bit or 8-bit character will be returned. Note that the read pointer is updated to the next character position after the read action. This routine is useful in successive reading of characters.

HSY\$CH_RPREV

HSY\$CH_RPREV reads the previous character.

Format

HSY\$CH_RPREV str,cur

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The previous character read.

Arguments

str

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified string. Note that this address must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

cur

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: modify
mechanism: by reference

The address of the current position of the specified current character. Note that this address must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

Description

This routine reads the previous character. Note that the current character pointer is updated. It points to the previous character position after the read action.

HSY\$CH_WCHAR

HSY\$CH_WCHAR

HSY\$CH_WCHAR writes a specified character to the current position of a buffer.

Format

HSY\$CH_WCHAR chr,cur

Arguments

chr

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The character to be written to the specified current position of the string.

cur

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the current position of the string where the input character is to be written to.

Description

This routine writes a specified character to the current position. It does not perform checking of writing past the end of buffer.

HSY\$CH_WNEXT

HSY\$CH_WNEXT writes a specified character to the current position of a buffer.

Format

HSY\$CH_WNEXT chr,cur

Arguments

chr

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The character to be written to the specified current position of the string.

cur

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: modify
mechanism: by reference

The address of the current position of the string where the input character is to be written to.

Description

This routine writes a specified character to the current position. It does not perform checking of writing past the end of buffer. Note that the write pointer **cur** is updated to the next character position after the write action.

HSY\$DX_RCHAR

HSY\$DX_RCHAR

HSY\$DX_RCHAR reads the current character.

Format

HSY\$DX_RCHAR str,[pos]

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

FFFF (hex) - Routine completed unsuccessfully.
non FFFF (hex) - The current character.

Arguments

str

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

The input string to be read.

pos

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by reference

Byte position from the starting position of the specified string which is used to indicate the current position. Note that this position must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

Description

This routine reads a character at the current character position as specified by **pos**. If **pos** is not specified, the first character of the string will be read. FFFF (hex) will be returned if **pos** is less than 1 or an invalid descriptor is specified by **str**.

HSY\$DX_RNEXT

HSY\$DX_RNEXT reads the current character.

Format

HSY\$DX_RNEXT str,[pos]

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

FFFF (hex) - Routine completed unsuccessfully.
non FFFF (hex) - The current character.

Arguments

str

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

The input string to be read.

pos

VMS Usage: longword_signed
type: longword integer (signed)
access: modify
mechanism: by reference

Byte position from the starting position of the specified string which is used to indicate the current position. Note that this position must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

Description

This routine reads a character at the current character position as specified by **pos**. If **pos** is not specified, the first character of the string will be read. FFFF (hex) will be returned if **pos** is less than 1 or an invalid descriptor is specified by **str**. Note that **pos** is updated to the next character position after the read action. This routine is useful for successive reading of characters.

HSY\$DX_WCHAR

HSY\$DX_WCHAR

HSY\$DX_WCHAR writes a specified character.

Format

HSY\$DX_WCHAR chr,str,[pos]

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The return status.

0 - Unsuccessful write caused by either invalid descriptor specified or **pos** less than 1.
SS\$_NORMAL - Successful write.

Arguments

chr

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by reference

The character to be written.

str

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

The specified string.

pos

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by reference

Byte position from the starting position of the specified string which indicates the position to where the input character is written.

Description

This routine writes a specified character to the current character position in the buffer. If **pos** is not specified, the character will be written to the start of the input string.

HSY\$DX_WNEXT

HSY\$DX_WNEXT writes a specified character.

Format

HSY\$DX_WNEXT chr,str,[pos]

Returns

VMS Usage: longword_signed
 type: longword integer (signed)
 access: write only
 mechanism: by value

The return status.

0 - Unsuccessful write caused by either invalid descriptor specified or **pos** less than 1.

SS\$_NORMAL - Successful write.

Arguments

chr

VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: read only
 mechanism: by reference

The character to be written.

str

VMS Usage: char_string
 type: character string
 access: read only
 mechanism: by descriptor

The specified string.

pos

VMS Usage: longword_signed
 type: longword integer (signed)
 access: modify
 mechanism: by reference

Byte position from the starting position of the specified string which indicates the position to where the input character is written.

Description

This routine writes a specified character to the current character position in the buffer. If **pos** is not specified, the character will be written to the start of the input string. Note that **pos** is updated after the write action. It points to the next character position after writing. This routine is useful for successful writing of character.

HSY\$CH_CURR

HSY\$CH_CURR

HSY\$CH_CURR points to the first byte of the current character.

Format

HSY\$CH_CURR str,cur

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The address of the first byte of the current character.

Arguments

str

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the input string. Note that this address must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

cur

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the current position of the specified current character. Note that **cur** may not point to the first byte of a multi-byte character if the current character is a multi-byte character.

Description

This routine provides the function of locating a character pointer on the proper character boundary if the current character is a multi-byte character. It checks if **cur** is specifying a position before **str**. It also checks if the current character is a 7-bit or 8-bit control character. In both cases, **cur** will be returned to the caller.

str can contain one-byte and multi-byte characters.

HSY\$CH_NEXT

HSY\$CH_NEXT points to the first byte of the next character.

Format

HSY\$CH_NEXT cur

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The address of the first byte of the next character.

Arguments

cur
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the first byte of the current character. Note that this character pointer must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

Description

This routine does not check if the next character position contains garbage or if it is passing beyond the buffer end since no buffer end position is specified.

HSY\$CH_PREV

HSY\$CH_PREV

HSY\$CH_PREV points to the first byte of the previous character.

Format

HSY\$CH_PREV str,cur

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The address of the first byte of the previous character.

Arguments

str

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the input string. Note that this address must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

cur

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the current position of the current character. Note that this character pointer must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

Description

This routine checks if the previous character position appears before the starting position of the input string. It also checks if the previous character is a 7-bit or 8-bit control character. In both cases, **cur** will be returned to the caller.

str can contain one-byte and multi-byte characters.

HSY\$DX_POS_CURR

HSY\$DX_POS_CURR points to the first byte of the current character.

Format

HSY\$DX_POS_CURR str,pos

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The return byte position.

- 0 - Procedure completed unsuccessfully.
- Non-zero - Byte position from the starting position of the input string that points to the first byte of the current character.

Arguments

str

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

Input string.

pos

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by reference

Byte position from the starting position of the input string which indicates the position of the current character. Note that this position may not be on the proper character boundary, e.g. it may point to the second byte of a two-byte character.

Description

HSY\$DX_POS_CURR lets you position the character pointer at the first byte of a multi-byte character. E.g. if **pos** is pointing to the second byte of a two-byte character, **HSY\$DX_POS_CURR** will return the byte position of the first byte of the two-byte character.

str can contain one-byte and multi-byte characters.

HSY\$DX_POS_NEXT

HSY\$DX_POS_NEXT

HSY\$DX_POS_NEXT points to the first byte of the next character.

Format

HSY\$DX_POS_NEXT str,pos

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The return byte position.

- 0 - Procedure completed unsuccessfully.
- Non-zero - Byte position from the starting position of the input string that points to the first byte of the next character.

Arguments

str

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

Input string.

pos

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by reference

Byte position from the starting position of the input string which indicates the position of the current character. Note that this position need not be on the proper character boundary, e.g. it may point to the second byte of a two-byte character.

Description

This routine allows **pos** to point at a non-character boundary position. If **pos** is pointing to the second byte of a two-byte character, the two-byte character will be treated as the current character and the next character will be returned to the caller. This routine does not check if **pos** is beyond the end of the string.

str can contain one-byte and multi-byte characters.

HSY\$DX_POS_PREV

HSY\$DX_POS_PREV points to the first byte of the previous character.

Format

HSY\$DX_POS_PREV str,pos

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The return byte position.

- 0 - Procedure completed unsuccessfully.
- Non-zero - Byte position from the starting position of the specified input string that points to the first byte of the previous character.

Arguments

str

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

Input string.

pos

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by reference

Byte position from the starting position of the specified input string which indicates the position of the current character. Note that this position need not be on the proper character boundary, e.g. it may point to the second byte of a two-byte character.

Description

This routine allows **pos** to point at a non-character boundary position. If **pos** is pointing to the second byte of a two-byte character, the two-byte character will be treated as the current character and the previous character will be returned to the caller. This routine does not check if **pos** is beyond the end of the string.

str can contain one-byte and multi-byte characters.

HSY\$DX_SKPC

HSY\$DX_SKPC

HSY\$DX_SKPC skips a specified character.

Format

HSY\$DX_SKPC chr,str

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The return byte position.

- 0 - Procedure completed unsuccessfully. It can either be skipped character not found or corrupted descriptor specified.
- Non-zero - Byte position from the starting position of the input string that points to the first character that does not match **chr**.

Arguments

chr

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

The specified input character to be skipped.

str

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

Input string.

Description

This routine skips the specified character **chr** at the start of the input string **str**. The position of the first character that does not match with the specified character **chr** will be returned to the caller.

str and **chr** can contain one-byte and multi-byte characters. If **chr** contains more than one characters, only the first character specified by the descriptor will be used.

HSY\$POS_CURR

HSY\$POS_CURR points to the first byte of the current character.

Format

HSY\$POS_CURR str,cur,end

Returns

VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: write only
 mechanism: by value

The address of the first byte of the current character.

Arguments

str

VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: read only
 mechanism: by value

The address of the starting position of the input string. Note that this address must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

cur


VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: read only
 mechanism: by value

The address of the current position of the specified current character. Note that this character pointer may not be on the proper character boundary, e.g. it may point to the second byte of a two-byte character.

end

VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: read only
 mechanism: by value

The address of the string terminating position plus one as illustrated below:



HSY\$POS_CURR

Description

This routine provides the function of locating a character pointer on the proper character boundary of a multi-byte character.

str can contain one-byte and multi-byte characters.

HSY\$POS_NEXT

HSY\$POS_NEXT points to the first byte of the next character.

Format

HSY\$POS_NEXT cur,end

Returns

VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: write only
 mechanism: by value

The address of the first byte of the next character.

Arguments

cur


VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: read only
 mechanism: by value

The address of the current position of the specified current character. Note that this address must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

end

VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: read only
 mechanism: by value

The address of the string terminating position plus one as illustrated below:



Description

This routine provides more checking than **HSY\$CH_NEXT**. If **cur** is greater than or equal to **end**, **cur** will be returned to the caller. If **cur** is pointing at a single-byte 7-bit or 8-bit control character, **cur+1** will be returned. If **cur** is pointing at a 8-bit character which is at the end of the input string, **end** will be returned. In general, if **cur** is pointing at an invalid character (e.g. a single 8-bit followed by a control character), it will skip the invalid character and return the next character position.

str can contain one-byte and multi-byte characters.

HSY\$POS_PREV

HSY\$POS_PREV

HSY\$POS_PREV points to the first byte of the previous character.

Format

HSY\$POS_PREV str,cur,end

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The address of the previous character of the specified current character.

Arguments

str

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the input string. Note that this address must be on the proper byte boundary, e.g. it should not point to the second byte of a two-byte character.

cur

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the current position of the string. Note that this character pointer must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

end

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the string terminating position plus one as illustrated below:

```
+---+---+      +---+---+---+---+
|   |   |      |   |   |   |   |
+---+---+      +---+---+---+---+
  ^                ^
  str              end
```

Description

This routine provides more checking than **HSY\$CH_PREV**. If **cur** is outside the range of the string as specified by **str** and **end**, no previous character position will be returned. Instead, **cur** will be returned to the caller.

str can contain one-byte and multi-byte characters.

HSY\$SKPC

HSY\$SKPC

HSY\$SKPC skips a specified character.

Format

HSY\$SKPC chr,str,len

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The return address.

- 0 - The specified character is not found in the string.
- Non-zero - The address of the position of the first character that does not match **chr**.

Arguments

chr

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The specified character to be skipped.

str

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the input string. Note that this address must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

len

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the input string.

Description

This routine skips the specified character **chr** at the start of the input string **str**. The address of the first character that does not match with the specified character **chr** will be returned to the caller.

str can contain one-byte and multi-byte characters.

HSY\$COMPARE

HSY\$COMPARE compares two specified strings.

Format

HSY\$COMPARE str1,len1,str2,len2

Returns

VMS Usage: longword_signed
 type: longword integer (signed)
 access: write only
 mechanism: by value

The return status.

- 1 - **str1** is less than **str2**.
- 0 - **str1** is equal to **str2**.
- 1 - **str1** is greater than **str2**.

Arguments

str1

VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: read only
 mechanism: by value

The address of the starting position of the first string for comparison.

len1

VMS Usage: longword_signed
 type: longword integer (signed)
 access: read only
 mechanism: by value

The length in bytes of **str1**.

str2

VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: read only
 mechanism: by value

The address of the starting position of second string for comparison.

len2

VMS Usage: longword_signed
 type: longword integer (signed)
 access: read only
 mechanism: by value

The length in bytes of **str2**.

HSY\$COMPARE

Description

str1 and **str2** can contain one-byte and multi-byte characters.

If the two input strings have different length, the shorter one is padded with space for comparison.

HSY\$DX_STR_EQUAL

HSY\$DX_STR_EQUAL checks if two specified character strings are equal.

Format

HSY\$DX_STR_EQUAL str1,str2,[conv-flag]

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The return status.

- 0 - The two strings are unequal.
- 1 - The two strings are equal.

Arguments

str1

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

First input string to be compared.

str2

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

Second input string to be compared.

conv-flag

VMS Usage: byte_signed
type: byte integer (signed)
access: read only
mechanism: by reference

Conversion flag indicating what conversion is done before comparing characters. Only bit 0 to bit 1 of this flag is used.

- Bit 0 = 0: Performs uppercasing conversion. Uppercasing can be done to both full form and half form letters.
- Bit 1 = 0: Performs full form to half form conversion.

No conversion will be done prior to comparing the characters if this optional parameter is not specified.

HSY\$DX_STR_EQUAL

Description

str1 and **str2** can contain one-byte and multi-byte characters.

If the number of characters in the two input strings are not equal, the shorter string is padded with space for comparison.

HSY\$STR_EQUAL

HSY\$STR_EQUAL checks if two specified character strings are equal.

Format

HSY\$STR_EQUAL str1,len1,str2,len2,[conv-flag]

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The return status.

- 0 - The two strings are unequal.
- 1 - The two strings are equal.

Arguments

str1

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the first input string to be compared.

len1

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of **str1**.

str2

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the second input string to be compared.

len2

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of **str2**.

HSY\$STR_EQUAL

conv-flag

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

Conversion flag indicating what conversion is done before comparing characters. Only bit 0 to bit 1 of this flag is used.

Bit 0 = 0: Performs uppercasing conversion. Uppercasing can be done to both full form and half form letters.

Bit 1 = 0: Performs full form to half form conversion.

No conversion will be done prior to comparing the characters if this optional parameter is not specified.

Description

str1 and **str2** can contain one-byte and multi-byte characters.

If the number of characters in the two input strings are not equal, the shorter string is padded with space for comparison.

HSY\$DX_LOCC

HSY\$DX_LOCC locates the position of the first occurrence of the specified character.

Format

HSY\$DX_LOCC chr,str

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The return byte position.

- 0 - Cannot locate the specified character in the specified string. It may be due to invalid descriptor specified or no such character found in the specified string.
- Non-zero - Byte position from the starting position of the specified string which indicates the position of the first occurrence of the specified character.

Arguments

chr

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

The character to be located in the specified string.

str

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

The specified string.

Description

chr can either be one-byte or multi-byte character. If a character string is specified by **chr**, only the first character in the string will be used.

str can contain one-byte and multi-byte characters.

HSY\$DX_POSITION

HSY\$DX_POSITION

HSY\$DX_POSITION searches the first occurrence of a substring in a specified string.

Format

HSY\$DX_POSITION str,sub-str,[pos]

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The return byte position.

- 0 - Procedure completed unsuccessfully.
- Non-zero - Byte position from the starting position of the input string which indicates the position containing the first byte of the first character of the substring found.

Arguments

str

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

Input string.

sub-str

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

The substring to be located in the input string.

pos

VMS Usage: word_signed
type: word integer (signed)
access: read only
mechanism: by reference

Byte position from the starting position of the input string which indicates the starting position for searching the substring. If this optional argument is not supplied, the searching will start from the beginning of the input string.

Description

str and **sub-str** can contain one-byte and multi-byte characters.

HSY\$DX_STR_SEARCH

HSY\$DX_STR_SEARCH searches the first occurrence of a specified substring in the input string.

Format

HSY\$DX_STR_SEARCH str,sub-str,[pos],[conv-flag]

Returns

VMS Usage: longword_signed
 type: longword integer (signed)
 access: write only
 mechanism: by value

The return byte position.

- 0 - Procedure completed unsuccessfully.
- Non-zero - Byte position from the starting position of the input string which indicates the first byte of the first character of the substring found.

Arguments

str

VMS Usage: char_string
 type: character string
 access: read only
 mechanism: by descriptor

Input string.

sub-str

VMS Usage: char_string
 type: character string
 access: read only
 mechanism: by descriptor

The specified substring to be searched.

pos

VMS Usage: word_signed
 type: word integer (signed)
 access: read only
 mechanism: by reference

Byte position from the starting position of the input string which indicates the starting position for searching the substring. If this optional argument is not supplied, the searching will start from the beginning of the input string.

conv-flag

VMS Usage: byte_signed
 type: byte integer (signed)
 access: read only
 mechanism: by reference

HSY\$DX_STR_SEARCH

Conversion flag indicating what conversion is done before comparing the characters. Only bit 0 to bit 1 of this flag are used.

Bit 0 = 0: Performs uppercasing conversion. Uppercasing can be done to both full form and half form letters.

Bit 1 = 0: Performs full form to half form conversion.

No conversion will be done prior to comparing the characters if this optional parameter is not specified.

Description

str and **sub-str** can contain one-byte and multi-byte characters.

HSY\$DX_STR_START

HSY\$DX_STR_START checks if the specified substring is found in another input string and starts from the first byte of the input string.

Format

HSY\$DX_STR_START str,sub-str,[conv-flag]

Returns

VMS Usage: longword_signed
 type: longword integer (signed)
 access: write only
 mechanism: by value

The return status.

- 0 - The two strings are equal. Cannot find the substring starting from the start of the input string.
- 1 - Finds the substring starting from the start of the input string.

Arguments

str

VMS Usage: char_string
 type: character string
 access: read only
 mechanism: by descriptor

Input string.

sub-str

VMS Usage: char_string
 type: character string
 access: read only
 mechanism: by descriptor

Substring to be located.

conv-flag

VMS Usage: byte_signed
 type: byte integer (signed)
 access: read only
 mechanism: by reference

Conversion flag indicating what conversion is done before comparing the characters. Only bit 0 to bit 1 of this flag are used.

- Bit 0 = 0: Performs uppercasing conversion. Uppercasing can be done to both full form and half form letters.
- Bit 1 = 0: Performs full form to half form conversion.

No conversion will be done prior to comparing the characters if this optional parameter is not specified.

HSY\$DX_STR_START

Description

str and **sub-str** can contain one-byte and multi-byte characters.

HSY\$LOCC

HSY\$LOCC locates the position of the first occurrence of the specified character.

Format

HSY\$LOCC chr,str,len

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The returned character pointer.

- 0 - No such character found in the specified string.
- Non-zero - The address of the position of the first occurrence of the specified character found in the input string.

Arguments

chr

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The specified character to be located in the input string.

str

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: modify
mechanism: by value

The address of the starting position of the input string.

len

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the input string.

Description

chr can either be one-byte or multi-byte character.

HSY\$POSITION

HSY\$POSITION

HSY\$POSITION searches the first occurrence of a specified substring in the input string.

Format

HSY\$POSITION str,str-len,sub-str,sub-str-len

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The return address.

- 0 - The specified substring is not found in the input string.
- Non-zero - The address of the starting position of the substring located in the input string.

Arguments

str

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the input string.

str-len

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of **str**.

sub-str

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified substring to be located.

sub-str-len

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of **sub-str**.

Description

str and **sub-str** can contain one-byte and multi-byte characters.

HSY\$STR_SEARCH

HSY\$STR_SEARCH

HSY\$STR_SEARCH searches the first occurrence of a specified substring in the input string with conversion performed prior to comparing the characters.

Format

HSY\$STR_SEARCH str,str-len,sub-str,sub-str-len,
conv-flag

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The return address.

- 0 - The specified substring is not found in the input string.
- Non-zero - The address of the starting position of the substring located in the input string.

Arguments

str

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the input string.

str-len

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of **str**.

sub-str

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified substring.

sub-str-len

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of **sub-str**.

conv-flag

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

Conversion flag indicating what conversion is done before comparing the characters. Only bit 0 to bit 1 of this flag are used.

Bit 0 = 0: Performs uppercasing conversion. Uppercasing can be done to both full form and half form letters.

Bit 1 = 0: Performs full form to half form conversion.

Description

str and **sub-str** can contain one-byte and multi-byte characters.

HSY\$STR_START

HSY\$STR_START

HSY\$STR_START checks if the specified substring is found in another input string and starts from the first byte of the input string.

Format

HSY\$STR_START str,str-len,sub-str,sub-str-len,
[conv-flag]

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned status.

- 0 - Cannot find the substring starting from the start of the input string.
- 1 - Finds the substring starting from the start of the input string.

Arguments

str

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the input string.

str-len

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the **str**.

sub-str

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the substring.

sub-str-len

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of **sub-str**.

conv-flag

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

Conversion flag indicating what conversion is done before comparing the characters. Only bit 0 to bit 1 of this flag is used.

Bit 0 = 0: Performs uppercasing conversion. Uppercasing can be done to both full form and half form letters.

Bit 1 = 0: Performs full form to half form conversion.

No conversion will be done prior to comparing the characters if this optional parameter is not specified.

Description

str and **sub-str** can contain one-byte and multi-byte characters.

HSY\$CH_NBYTE

HSY\$CH_NBYTE

HSY\$CH_NBYTE counts the number of bytes of a character string.

Format

HSY\$CH_NBYTE str,nof-chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The number of bytes counted in the specified number of characters.

Arguments

str

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified string.

nof-chr

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The number of characters to be scanned from the starting position of the input string for counting the number of bytes.

Description

The routine accepts the number of characters and returns the number of bytes contained in the string of characters.

HSY\$CH_NCHAR

HSY\$CH_NCHAR returns the number of characters in a specified string.

Format

HSY\$CH_NCHAR str,len

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The number of characters in the specified string.

Arguments

str

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified string. Note that this address must be on the proper character boundary, e.g. it should not point to the second byte of a two-byte character.

len

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in byte of the specified string.

Description

This routine returns the number of characters found in the input string up to the position specified by **len**. All one-byte 7-bit control characters and one-byte 8-bit characters (e.g. an 8-bit character followed by a 7-bit control character) are treated as a character. If the last character specified by **len** is a multi-byte character with its last byte located beyond the input string terminating position as specified by **len**, this multi-byte character is also counted by the routine.

HSY\$CH_SIZE

HSY\$CH_SIZE

HSY\$CH_SIZE tells the byte length of the specified character.

Format

HSY\$CH_SIZE chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The size in bytes of the specified character.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

This routine returns the number of bytes of the specified character. If the character is an ASCII character, 1 will be returned. If it is a multi-byte character, the number of bytes of the character will be returned.

HSY\$DX_NOF_BYTE

HSY\$DX_NOF_BYTE counts the number of bytes of a character string.

Format

HSY\$DX_NOF_BYTE str,nof-chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned number of bytes.

0 - Procedure completed unsuccessfully due to either invalid descriptor specified or **nof-chr** less than 1.

Non-zero - The number of bytes.

Arguments

str

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

Input string.

nof-chr

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by reference

The number of characters to be scanned from the starting position of the input string for counting the number of bytes.

Description

This routine accepts the number of characters and returns the number of bytes contained in the string of characters.

HSY\$DX_NOF_CHAR

HSY\$DX_NOF_CHAR

HSY\$DX_NOF_CHAR returns the number of characters in a specified number of bytes.

Format

HSY\$DX_NOF_CHAR str

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned number of characters.

- 0 - Procedure completed unsuccessfully due to either invalid descriptor specified or **nof-chr** less than 1.
- Non-zero - The number of characters.

Arguments

str
VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

Input string.

Description

This routine returns the number of characters found in the input string up to the position specified by the length field of the descriptor. All one-byte 7-bit control characters and one-byte 8-bit characters (e.g. an 8-bit character followed by a 7-bit control character) are treated as a character. If the last character specified by the length field of the descriptor is a multi-byte character with its last byte located beyond the input string terminating position, this multi-byte character is also counted by the routine.

HSY\$IS_ALPHA

HSY\$IS_ALPHA checks if the input character is a Greek or Roman letter.

Format

HSY\$IS_ALPHA chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

- 0 - The input character is not a letter character.
- 1 - The input character is a letter character.

Note that "letter character" here means one of the following:

- (1) one-byte English letter
- (2) multi-byte English letter
- (3) multi-byte Greek letter

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

None.

HSY\$IS_DESCRIPTION

HSY\$IS_DESCRIPTION

HSY\$IS_DESCRIPTION checks if the input character is a multi-byte local language punctuation (excluding parenthesis, bracket and quote).

Format

HSY\$IS_DESCRIPTION chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

- 0 - The input character is not a multi-byte local language punctuation (excluding parenthesis, bracket and quote).
- 1 - The input character is a multi-byte local language punctuation (excluding parenthesis, bracket and quote).

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

None.

HSY\$IS_DIGIT

HSY\$IS_DIGIT checks if the input character is a one-byte or multi-byte numeric digit.

Format

HSY\$IS_DIGIT chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

0 - The input character is not a digit symbol.

1 - The input character is a digit symbol.

Arguments

chr

VMS Usage: longword_unsigned
type: longword integer(unsigned)
access: read only
mechanism: by value

Input character.

Description

None.

HSY\$IS_GENERAL

HSY\$IS_GENERAL

HSY\$IS_GENERAL checks if the input character is a multi-byte general symbol character (that does not belong to any of the above categories).

Format

HSY\$IS_GENERAL chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

- 0 - The input character is not a multi-byte general symbol character.
- 1 - The input character is a multi-byte general symbol character.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

None.

HSY\$IS_GREEK

HSY\$IS_GREEK checks if the input character is a multi-byte Greek letter.

Format

HSY\$IS_GREEK chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

- 0 - The input character is not a multi-byte Greek letter.
- 1 - The input character is a multi-byte Greek letter.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

None.

HSY\$IS_IDEOGRAPH

HSY\$IS_IDEOGRAPH

HSY\$IS_IDEOGRAPH checks if the input multi-byte character is an ideographic multi-byte character (excluding all multi-byte Roman and Greek letters, Japanese characters and all multi-byte symbols).

Format

HSY\$IS_IDEOGRAPH chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

- 0 - The input character is not an ideographic multi-byte character.
- 1 - The input character is an ideographic multi-byte character.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

None.

HSY\$IS_LEFT_PARENTHESIS

HSY\$IS_LEFT_PARENTHESIS checks if the input character is a multi-byte left parenthesis symbol character.

Format

HSY\$IS_LEFT_PARENTHESIS chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

- 0 - The input character is not a multi-byte left parenthesis symbol character.
- 1 - The input character is a multi-byte left parenthesis symbol character.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

None.

HSY\$IS_LINE_DRAWING

HSY\$IS_LINE_DRAWING

HSY\$IS_LINE_DRAWING checks if the input character is a multi-byte line drawing symbol character.

Format

HSY\$IS_LINE_DRAWING chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

- 0 - The input character is not a multi-byte line drawing symbol character.
- 1 - The input character is a multi-byte line drawing symbol character.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

None.

HSY\$IS_LOWER

HSY\$IS_LOWER checks if the input character is a lower case Greek or Roman letter.

Format

HSY\$IS_LOWER chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

0 - The input character is not a lower case letter character.

1 - The input character is a lower case letter character.

Note that "letter character" here means one of the following:

- (1) one-byte English letter
- (2) multi-byte English letter
- (3) multi-byte Greek letter

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

None.

HSY\$IS_NO_FIRST

HSY\$IS_NO_FIRST

HSY\$IS_NO_FIRST checks if the input character is a multi-byte "NO FIRST" character.

Format

HSY\$IS_NO_FIRST chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

- 0 - The input character is not a multi-byte "NO FIRST" character.
- 1 - The input character is a multi-byte "NO FIRST" character.

Arguments

chr

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

"NO FIRST" multi-byte characters include right parenthesis, right bracket, right quote as well as some multi-byte punctuations that should not appear at the start of a line.

HSY\$IS_NO_LAST

HSY\$IS_NO_LAST checks if the input character is a multi-byte "NO-LAST" character.

Format

HSY\$IS_NO_LAST chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

- 0 - The input character is not a multi-byte "NO LAST" character.
- 1 - The input character is a multi-byte "NO LAST" character.

Arguments

chr

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

"NO LAST" multi-byte characters include left parenthesis, left bracket and left quote.

HSY\$IS_PARENTHESIS

HSY\$IS_PARENTHESIS

HSY\$IS_PARENTHESIS checks if the input character is a multi-byte parenthesis symbol character.

Format

HSY\$IS_PARENTHESIS chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

- 0 - The input character is not a multi-byte parenthesis symbol character.
- 1 - The input character is a multi-byte parenthesis symbol character.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

Multi-byte parenthesis symbols include left and right multi-byte parentheses.

HSY\$IS_RIGHT_PARENTHESIS

HSY\$IS_RIGHT_PARENTHESIS checks if the input character is a multi-byte right parenthesis symbol character.

Format

HSY\$IS_RIGHT_PARENTHESIS chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

- 0 - The input character is not a multi-byte right parenthesis symbol character.
- 1 - The input character is a multi-byte right parenthesis symbol character.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

None.

HSY\$IS_ROMAN

HSY\$IS_ROMAN

HSY\$IS_ROMAN checks if the input character is a one-byte or multi-byte English letter.

Format

HSY\$IS_ROMAN chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

- 0 - The input character is not a one-byte or multi-byte English letter.
- 1 - The input character is a one-byte or multi-byte English letter.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

None.

HSY\$IS_TECHNICAL

HSY\$IS_TECHNICAL checks if the input character is a scientific or mathematical multi-byte symbol character.

Format

HSY\$IS_TECHNICAL chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

- 1 - The input character is a technical multi-byte symbol character.
- 0 - The input character is not a technical multi-byte symbol character.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

None.

HSY\$IS_UNIT

HSY\$IS_UNIT

HSY\$IS_UNIT checks if the input character is a multi-byte standard unit symbol character.

Format

HSY\$IS_UNIT chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

- 0 - The input character is not a multi-byte standard unit symbol character.
- 1 - The input character is a multi-byte standard unit symbol character.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

None.

HSY\$IS_UPPER

HSY\$IS_UPPER checks if the input character is an upper case Greek or Roman letter.

Format

HSY\$IS_UPPER chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

- 0 - The input character is not an upper case letter character.
- 1 - The input character is an upper case letter character.

Note that "letter character" here means one of the following:

- (1) one-byte English letter
- (2) multi-byte English letter
- (3) multi-byte Greek letter

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

None.

HSY\$IS_VALID

HSY\$IS_VALID

HSY\$IS_VALID checks if the input character is a valid multi-byte character.

Format

HSY\$IS_VALID chr

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

The returned flag.

- 0 - The input character is not a valid multi-byte character.
- 1 - The input character is a valid multi-byte character.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

Valid multi-byte characters are those found in the DEC supported local language character set.

HSY\$DX_DATE_TIME

HSY\$DX_DATE_TIME returns the date and time in local language format (the time can either be the system time or the user-specified date).

Format

HSY\$DX_DATE_TIME dst,[flag],[time-addr]

Returns

VMS Usage: cond_value
 type: longword (unsigned)
 access: write only
 mechanism: by value

The same condition value returned by the OpenVMS Run Time Library routine LIB\$SCOPY_R_DX.

Arguments

dst

VMS Usage: char_string
 type: character string
 access: write only
 mechanism: by descriptor

The specified destination string to store the resulting time string in local language format.

flag

VMS Usage: byte_signed
 type: byte integer (signed)
 access: read only
 mechanism: by reference

Bit 0: 0 - 12 hour format (default)
 1 - 24 hour format

Bit 1: 0 - Full date and time (default)
 1 - Time only

If this argument is not specified, 0 will be used which means 12 hour format with full date and time display.

time-addr

VMS Usage: longword_unsigned
 type: longword integer (unsigned)
 access: read only
 mechanism: by value

The address of the quadword that contains the user-specified date and time in 64-bit time format. If this argument is not specified, the current system time will be used.

HSY\$DX_DATE_TIME

Description

None.

HSY\$DX_TIME

HSY\$DX_TIME returns the date and time of the system time in local language format.

Format

HSY\$DX_TIME dst,[flag]

Returns

VMS Usage: cond_value
type: longword (unsigned)
access: write only
mechanism: by value

The same condition value returned by the OpenVMS Run Time Library routine LIB\$SCOPY_R_DX.

Arguments

dst

VMS Usage: char_string
type: character string
access: write only
mechanism: by descriptor

The specified destination string to store the resulting displaying string in local language format.

flag

VMS Usage: byte_signed
type: byte integer (signed)
access: read only
mechanism: by reference

Bit 0: 0 - 12 hour format (default)
1 - 24 hour format

Bit 1: 0 - Full date and time (default)
1 - Time only

If this argument is not specified, 0 will be used which means 12 hour format with full date and time display.

Description

None.

HSY\$CHG_GENERAL

HSY\$CHG_GENERAL

HSY\$CHG_GENERAL converts specified characters in one of the three following ways:

- (1) From lower case letters to upper case letters (including English and Greek)
- (2) From full form ASCII to half form ASCII

Format

HSY\$CHG_GENERAL chr,conv-flag

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The converted character.

Arguments

chr

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The specified character to be converted.

conv-flag

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

Conversion flag indicating what conversion is to be done. Only bit 0 to bit 1 of this flag is used.

Bit 0 = 0: Performs uppercasing conversion. Uppercasing can be done to both full form and half form letters.

Bit 1 = 0: Performs full form to half form conversion.

Description

If **chr** is not applicable to a particular conversion, e.g. **chr** is not a letter and uppercasing conversion is specified by **conv-flag**, then no conversion will be done and **chr** will be returned.

HSY\$CHG_KEISEN

HSY\$CHG_KEISEN converts '0' to '9' and '-' to multi-byte line drawing characters.

Format

HSY\$CHG_KEISEN chr

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

Returned multi-byte line drawing character.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The input character code (see description).

Description

The conversion table is as follows:

If **chr** is not from '0' to '9' or '-', **chr** will be returned with no conversion done.

HSY\$CHG_ROM_CASE

HSY\$CHG_ROM_CASE

HSY\$CHG_ROM_CASE toggles the casing of one-byte and multi-byte letters (English letters and Greek letters) of the input character.

Format

HSY\$CHG_ROM_CASE chr

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

Converted character with its case toggled.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

One-byte and multi-byte English letters and multi-byte Greek letters contain both upper and lower case characters. This routine converts upper case characters to lower case characters and vice versa.

If **chr** is not a one-byte or multi-byte letter as stated above, **chr** will be returned and no conversion will be done.

HSY\$CHG_ROM_FULL

HSY\$CHG_ROM_FULL converts one-byte ASCII (half form ASCII) to multi-byte equivalence (full form ASCII).

Format

HSY\$CHG_ROM_FULL chr

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The corresponding full form ASCII character.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

If **chr** is not a half form ASCII character, **chr** will be returned and no conversion will be done.

HSY\$CHG_ROM_HALF

HSY\$CHG_ROM_HALF

HSY\$CHG_ROM_HALF converts multi-byte ASCII (full form ASCII) to one-byte (half form ASCII) equivalence.

Format

HSY\$CHG_ROM_HALF chr

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The corresponding half form ASCII character.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

If **chr** is not a full form character, **chr** will be returned and no conversion will be done.

HSY\$CHG_ROM_LOWER

HSY\$CHG_ROM_LOWER converts one-byte and multi-byte letters (English letters and Greek letters) to lower case.

Format

HSY\$CHG_ROM_LOWER chr

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The corresponding lowercase character.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

If **chr** is not an upper case letter (English letter and Greek letter), **chr** will be returned and no conversion will be done.

HSY\$CHG_ROM_SIZE

HSY\$CHG_ROM_SIZE

HSY\$CHG_ROM_SIZE toggles the form (full form or half form) of the input character.

Format

HSY\$CHG_ROM_SIZE chr

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

Toggled character.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

Full form and half form conversions only apply to one-byte ASCII (half form ASCII) and multi-byte ASCII (full form ASCII). There are no half form equivalence of other multi-byte characters such as Greek letters.

If **chr** is not a full form or half form character, **chr** will be returned and no conversion will be done.

HSY\$CHG_ROM_UPPER

HSY\$CHG_ROM_UPPER converts one-byte and multi-byte letters (English letters and Greek letters) to upper case.

Format

HSY\$CHG_ROM_UPPER chr

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

The corresponding uppercase character.

Arguments

chr
VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

Input character.

Description

If **chr** is not a lower case letter (English letter and Greek letter), **chr** will be returned and no conversion will be done.

HSY\$DX_TRA_ROM_CASE

HSY\$DX_TRA_ROM_CASE

HSY\$DX_TRA_ROM_CASE toggles the casing of one-byte and multi-byte letters (English letters and Greek letters) found in the input string.

Format

HSY\$DX_TRA_ROM_CASE dst,src,[len]

Returns

VMS Usage: cond_value
type: longword (unsigned)
access: write only
mechanism: by value

Arguments

dst

VMS Usage: char_string
type: character string
access: write only
mechanism: by descriptor

The destination string that stores the result of the conversion.

src

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

The source string that is to be converted.

len

VMS Usage: word_signed
type: word integer (signed)
access: write only
mechanism: by reference

The length in bytes of the converted string. If this argument is not supplied, no length information of the converted string will be returned to the caller.

Description

One-byte and multi-byte English letters and multi-byte Greek letters all contain both upper case and lower case characters. This routine converts all upper case characters to lower case and all lower case characters to upper case.

Characters in the input string that are not upper case or lower case characters are copied to the corresponding position in the output string with no conversion done.

condition values returned

LIB\$_INVSTRDES	Invalid string descriptor. A string descriptor has an invalid value in its DSC\$_CLASS field.
LIB\$_STRTRU	Procedure successfully completed. String truncated.
LIB\$_FATERRLIB	Fatal internal error. An internal consistency check has failed.
LIB\$_INSVIRMEM	Insufficient virtual memory.
SS\$_NORMAL	Procedure successfully completed.

HSY\$DX_TRA_ROM_FULL

HSY\$DX_TRA_ROM_FULL

HSY\$DX_TRA_ROM_FULL converts one-byte ASCII (half form ASCII) to multi-byte equivalence (full form ASCII).

Format

HSY\$DX_TRA_ROM_FULL dst,src,[len]

Returns

VMS Usage: cond_value
type: longword (unsigned)
access: write only
mechanism: by value

Arguments

dst

VMS Usage: char_string
type: character string
access: write only
mechanism: by descriptor

The destination string that stores the result of the conversion.

src

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

The source string that is to be converted.

len

VMS Usage: word_signed
type: word integer (signed)
access: write only
mechanism: by reference

The length in bytes of the converted string. If this argument is not supplied, no length information of the converted string will be returned to the caller.

Description

Characters in the input string that are not half form characters are copied to the corresponding position in the output string with no conversion done.

condition values returned

LIB\$_INVSTRDES	Invalid string descriptor. A string descriptor has an invalid value in its DSC\$B_CLASS field.
LIB\$_STRTRU	Procedure successfully completed. String truncated.

LIB\$_FATERRLIB

Fatal internal error. An internal consistency check has failed.

LIB\$_INSVIRMEM

Insufficient virtual memory.

SS\$_NORMAL

Procedure successfully completed.

HSY\$DX_TRA_ROM_HALF

HSY\$DX_TRA_ROM_HALF

HSY\$DX_TRA_ROM_HALF converts multi-byte ASCII (full form ASCII) to one-byte (half form ASCII) equivalence.

Format

HSY\$DX_TRA_ROM_HALF dst,src,[len]

Returns

VMS Usage: cond_value
type: longword (unsigned)
access: write only
mechanism: by value

Arguments

dst

VMS Usage: char_string
type: character string
access: write only
mechanism: by descriptor

The destination string that stores the result of the conversion.

src

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

The source string that is to be converted.

len

VMS Usage: word_signed
type: word integer (signed)
access: write only
mechanism: by reference

The length in bytes of the converted string. If this argument is not supplied, no length information of the converted string will be returned to the caller.

Description

Characters in the input string that are not full form characters are copied to the corresponding position in the output string with no conversion done.

CONDITION VALUES RETURNED

LIB\$_INVSTRDES	Invalid string descriptor. A string descriptor has an invalid value in its DSC\$B_CLASS field.
LIB\$_STRTRU	Procedure successfully completed. String truncated.

LIB\$_FATERRLIB

Fatal internal error. An internal consistency check has failed.

LIB\$_INSVIRMEM

Insufficient virtual memory.

SS\$_NORMAL

Procedure successfully completed.

HSY\$DX_TRA_ROM_LOWER

HSY\$DX_TRA_ROM_LOWER

HSY\$DX_TRA_ROM_LOWER converts one-byte and multi-byte letters (English letters and Greek letters) to lower case.

Format

HSY\$DX_TRA_ROM_LOWER dst,src,[len]

Returns

VMS Usage: cond_value
type: longword (unsigned)
access: write only
mechanism: by value

Arguments

dst

VMS Usage: char_string
type: character string
access: write only
mechanism: by descriptor

The destination string that stores the result of the conversion.

src

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

The source string that is to be converted.

len

VMS Usage: word_signed
type: word integer (signed)
access: write only
mechanism: by reference

The length in bytes of the converted string. If this argument is not supplied, no length information of the converted string will be returned to the caller.

Description

Characters in the input string that are not upper case letters are copied to the corresponding position in the output string with no conversion done.

condition values returned

LIB\$_INVSTRDES	Invalid string descriptor. A string descriptor has an invalid value in its DSC\$B_CLASS field.
LIB\$_STRTRU	Procedure successfully completed. String truncated.

HSY\$DX_TRA_ROM_LOWER

LIB\$_FATERRLIB

Fatal internal error. An internal consistency check has failed.

LIB\$_INSVIRMEM

Insufficient virtual memory.

SS\$_NORMAL

Procedure successfully completed.

HSY\$DX_TRA_ROM_SIZE

HSY\$DX_TRA_ROM_SIZE

HSY\$DX_TRA_ROM_SIZE toggles the form (full form or half form) of the input string.

Format

HSY\$DX_TRA_ROM_SIZE dst,src,[len]

Returns

VMS Usage: cond_value
type: longword (unsigned)
access: write only
mechanism: by value

Arguments

dst

VMS Usage: char_string
type: character string
access: write only
mechanism: by descriptor

The destination string that stores the result of the conversion.

src

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

The source string that is to be converted.

len

VMS Usage: word_signed
type: word integer (signed)
access: write only
mechanism: by reference

The length in bytes of the converted string. If this argument is not supplied, no length information of the converted string will be returned to the caller.

Description

Full form and half form conversions only apply to one-byte ASCII (half form ASCII) and multi-byte ASCII (full form ASCII). There is no half form equivalence of other multi-byte characters such as multi-byte Greek letters.

Characters in the input string that are not full form or half form characters are copied to the corresponding position in the output string with no conversion done.

condition values returned

LIB\$_INVSTRDES	Invalid string descriptor. A string descriptor has an invalid value in its DSC\$_CLASS field.
LIB\$_STRTRU	Procedure successfully completed. String truncated.
LIB\$_FATERRLIB	Fatal internal error. An internal consistency check has failed.
LIB\$_INSVIRMEM	Insufficient virtual memory.
SS\$_NORMAL	Procedure successfully completed.

HSY\$DX_TRA_ROM_UPPER

HSY\$DX_TRA_ROM_UPPER

HSY\$DX_TRA_ROM_UPPER converts one-byte and multi-byte letters (English letters and Greek letters) to upper case.

Format

HSY\$DX_TRA_ROM_UPPER dst,src,[len]

Returns

VMS Usage: cond_value
type: longword (unsigned)
access: write only
mechanism: by value

Arguments

dst

VMS Usage: char_string
type: character string
access: write only
mechanism: by descriptor

The destination string that stores the result of the conversion.

src

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

The source string that is to be converted.

len

VMS Usage: word_signed
type: word integer (signed)
access: write only
mechanism: by reference

The length in bytes of the converted string. If this argument is not supplied, no length information of the converted string will be returned to the caller.

Description

Characters in the input string that are not lower case letters are copied to the corresponding position in the output string with no conversion done.

condition values returned

LIB\$INVSTRDES	Invalid string descriptor. A string descriptor has an invalid value in its DSC\$B_CLASS field.
LIB\$_STRTRU	Procedure successfully completed. String truncated.

LIB\$_FATERRLIB

Fatal internal error. An internal consistency check has failed.

LIB\$_INSVIRMEM

Insufficient virtual memory.

SS\$_NORMAL

Procedure successfully completed.

HSY\$DX_TRA_SYMBOL

HSY\$DX_TRA_SYMBOL

HSY\$DX_\$TRA_SYMBOL converts the sequence of a one-byte character to a string of multi-byte symbols.

Format

HSY\$DX_\$TRA_SYMBOL dst,src,[len]

Returns

VMS Usage: cond_value
type: longword (unsigned)
access: write only
mechanism: by value

The return status.

Arguments

dst

VMS Usage: char_string
type: character string
access: write only
mechanism: by descriptor

The destination string that stores the result of the conversion.

src

VMS Usage: char_string
type: character string
access: read only
mechanism: by descriptor

The source string that is to be converted.

len

VMS Usage: word_signed
type: word integer (signed)
access: write only
mechanism: by reference

The length in bytes of the converted string. If this argument is not supplied, no length information of the converted string will be returned to the caller.

Description

This routine provides conversion of sequences of ASCII characters to corresponding multi-byte symbols and multi-byte characters as stated in the following table.

If the characters in the input string are not applicable for conversion, they will be copied to the corresponding position in the output string with no conversion done.

condition values returned

LIB\$_INVSTRDES	Invalid string descriptor. A string descriptor has an invalid value in its DSC\$_CLASS field.
LIB\$_STRTRU	Procedure successfully completed. String truncated.
LIB\$_FATERRLIB	Fatal internal error. An internal consistency check has failed.
LIB\$_INSVIRMEM	Insufficient virtual memory.
SS\$_NORMAL	Procedure successfully completed.

HSY\$TRA_ROM_CASE

HSY\$TRA_ROM_CASE

HSY\$TRA_ROM_CASE toggles the casing of one-byte and multi-byte letters (English letters and Greek letters) found in the string.

Format

HSY\$TRA_ROM_CASE ip,il,op,ol,rl

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

- 1 - The input string is successfully converted.
- 0 - A truncated input string is converted due to insufficient output space of the output string allocated by the caller.

Arguments

ip

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified string which is the input for conversion.

il

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the input string.

op

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified string which stores the output of conversion.

ol

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the output string.

rl

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by reference

The length in bytes of the converted string.

Description

One-byte and multi-byte English letters and multi-byte Greek letters contain both upper and lower case characters. This routine converts all upper case characters to lower case and all lower case characters to upper case.

If the characters in the input string are not one-byte or multi-byte letters, they will be copied to the corresponding position in the output string with no conversion done.

HSY\$TRA_ROM_FULL

HSY\$TRA_ROM_FULL

HSY\$TRA_ROM_FULL converts one-byte ASCII (half form ASCII) to multi-byte equivalence (full form ASCII).

Format

HSY\$TRA_ROM_FULL ip,il,op,ol,rl

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

- 1 - The input string is successfully converted.
- 0 - A truncated input string is converted due to insufficient output space of the output string allocated by the caller.

Arguments

ip

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified string which is the input for conversion.

il

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the input string.

op

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified string which stores the output of conversion.

ol

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the output string.

rl

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by reference

The length in bytes of the converted string.

Description

If the characters in the input string are not half form characters, they will be copied to the corresponding position in the output string with no conversion done.

HSY\$TRA_ROM_HALF

HSY\$TRA_ROM_HALF

HSY\$TRA_ROM_HALF converts multi-byte ASCII (full form ASCII) to one-byte (half form ASCII) equivalence.

Format

HSY\$TRA_ROM_HALF ip,il,op,ol,rl

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

- 1 - The input string is successfully converted.
- 0 - A truncated input string is converted due to insufficient output space of the output string allocated by the caller.

Arguments

ip

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified string which is the input for conversion.

il

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the input string.

op

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified string which stores the output of conversion.

ol

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the output string.

rl

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by reference

The length in bytes of the converted string.

Description

If the characters in the input string are not full form characters, they will be copied to the corresponding position in the output string with no conversion done.

HSY\$TRA_ROM_LOWER

HSY\$TRA_ROM_LOWER

HSY\$TRA_ROM_LOWER converts one-byte and multi-byte letters (English letters and Greek letters) to lower case.

Format

HSY\$TRA_ROM_LOWER ip,il,op,ol,rl

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

- 1 - The input string is successfully converted.
- 0 - A truncated input string is converted due to insufficient output space of the output string allocated by the caller.

Arguments

ip

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified string which is the input for conversion.

il

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the input string.

op

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified string which stores the output of conversion.

ol

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the output string.

rl

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by reference

The length in bytes of the converted string.

Description

If the characters in the input string are not upper case letters, they will be copied to the corresponding position in the output string with no conversion done.

HSY\$TRA_ROM_SIZE

HSY\$TRA_ROM_SIZE

HSY\$TRA_ROM_SIZE toggles the form (full form or half form) of the input string.

Format

HSY\$TRA_ROM_SIZE ip,il,op,ol,rl

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

- 1 - The input string is successfully converted.
- 0 - A truncated input string is converted due to insufficient output space of the output string allocated by the caller.

Arguments

ip

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified string which is the input for conversion.

il

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the input string.

op

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified string which stores the output of conversion.

ol

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the output string.

rl

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by reference

The length in bytes of the converted string.

Description

Full form and half form conversions only apply to one-byte ASCII (half form ASCII) and multi-byte ASCII (full form ASCII). There is no half form equivalence of other multi-byte characters such as Greek letters.

If the characters in the input string are not full form or half form characters, they will be copied to the corresponding position in the output string with no conversion done.

HSY\$TRA_ROM_UPPER

HSY\$TRA_ROM_UPPER

HSY\$TRA_ROM_UPPER converts one-byte and multi-byte letters (English letters and Greek letters) to upper case.

Format

HSY\$TRA_ROM_UPPER ip,il,op,ol,rl

Returns

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: write only
mechanism: by value

- 1 - The input string is successfully converted.
- 0 - A truncated input string is converted due to insufficient output space of the output string allocated by the caller.

Arguments

ip

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified string which is the input for conversion.

il

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the input string.

op

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the starting position of the specified string which stores the output of conversion.

ol

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length in bytes of the output string.

rl

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by reference

The length in bytes of the converted string.

Description

If the characters in the input string are not lower case letters, they will be copied to the corresponding positions in the output string with no conversion done.

HSY\$TRA_SYMBOL

HSY\$TRA_SYMBOL

HSY\$TRA_SYMBOL converts the sequence of a one-byte character to a string of multi-byte symbols.

Format

HSY\$TRA_SYMBOL ip,il,op,ol,rl

Returns

VMS Usage: longword_signed
type: longword integer (signed)
access: write only
mechanism: by value

- 0 - The conversion completed unsuccessfully.
- 1 - The conversion completed successfully.

Arguments

ip

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the specified input string that is to be converted.

il

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length of the input string that is specified by the argument **ip**.

op

VMS Usage: longword_unsigned
type: longword integer (unsigned)
access: read only
mechanism: by value

The address of the specified output string that stores the converted string.

ol

VMS Usage: longword_signed
type: longword integer (signed)
access: read only
mechanism: by value

The length of the output string that is specified by the argument **op**.

rl

VMS Usage: longword_signed
type: longword integer (signed)
access: write only

mechanism: by reference

The actual length of the converted string.

Description

This routine provides conversion of sequences of ASCII characters to corresponding multi-byte symbols and multi-byte characters as stated in the following table.

If the characters in the input string are not applicable for conversion, they will be copied to the corresponding position in the output string with no conversion done.

