

Software Product Description

PRODUCT NAME: PDP-11 C for RT-11, Version 1.2

SPD 09.33.03

DESCRIPTION

PDP-11 C for RT-11 is a product of Mentec, Inc. and is licensed under Digital Equipment Corporation's Standard Terms and Conditions.

PDP-11 C for RT-11 is a reliable language processor for Digital Equipment Corporation's proprietary operating systems on the PDP-11. PDP-11 C is highly compatible with the ANSI standard for the C language. PDP-11 C can be used to develop code for inclusion into low level system routines.

PDP-11 C for RT-11 consists of the compiler, a Run Time Library (RTL), and documentation.

The compiler produces machine code optimized for execution speed and memory efficiency. The compiler is highly compatible with the ANSI C standard, X3J11/90-013, February 14, 1990, and extends beyond ANSI requirements with several extensions for the PDP-11 family of central processors.

The compiler runs in native mode on the RT-11 mapped host systems and produces PDP-11 object code compatible for all the supported target systems. These target systems are RSX-11M, RSX-11S, RSX-11M-PLUS, Micro/RSX, RSTS/E, RT-11 (both mapped and unmapped monitors), and VAX-11 RSX. The Run-Time Library is provided in object form.

The Run-Time Library provides run-time support that allows the user to perform many needed functions not provided within the compiler itself. These features include:

- Native Standard I/O (STDIO) for each supported PDP-11 operating system
- Arithmetic Operations
- Character Handling
- Localization
- Signal Handling
- Variable Arguments
- String Handling

Features

- Compatible with the ANSI C Standard (February, 1990)
- Function prototypes for declaring and checking function argument count and types
- Structured programming control flow constructs
 - if...else construct for simple selection
 - switch statement for multi-choice selection with an arbitrary number of case statements
 - while, do, and for statements for iterative execution
- Flow modification statements:
 - break
 - continue
 - goto
- Data type for numeric, non-numeric, and systems programming:
 - Byte, word, and longword signed and unsigned integers
 - Integer constants in decimal, octal, and hexadecimal radices
 - Support for void data type
 - Single-character variables and constants
 - Single- and double-precision numbers
 - Pointer variables containing the addresses of other variables
 - Data aggregates including array, structures, and unions
 - User-defined or enumerated (enum) data types with forward referencing allowed
- Storage allocation using:
 - Auto, static, register and extern storage allocation classes for variables
 - Keywords (globalref, globaldef, and globalvalue) for sharing data among program modules

- Psect Pragma for control of data attributes and data placement
- Concise arithmetic, relational, and logical operators.
- Preprocessor control statements for:
 - File inclusion
 - Identifier substitution
 - Conditional compilation
 - Object module identification via pragmas
 - List File control via pragmas
 - Data storage control via pragmas
 - Source and list character sets via pragmas
- Separate compilation capabilities
- Compiler generated listing file including optional:
 - Expanded preprocessor substitution listing
 - MACRO-11 file
- Generated Code:
 - EIS or FPU
 - PIC or NONPIC
- Position Independent Code (PIC) Supervisor Mode Run-Time Library for the RSTS/E, RSX-11M-PLUS, and Micro/RSX target systems
- Full support of RSX Executive Directives on RSX target systems
- Support of RSX AST, RSX SST, and RSX CSM linkages to allow users to write:
 - Asynchronous system trap handlers
 - Synchronous system trap handlers
 - Supervisor mode library routines for RSX and RSTS/E systems

An Installation Verification Program (IVP) is provided to verify the installation of PDP-11 C and its RTL.

HARDWARE REQUIREMENTS

Any valid RT-11 Operating System configuration with:

- Minimum of 128K bytes of user memory
- At least 4,000 blocks, 1,000 of which must be contiguous at compile-time
- At least 4,000 blocks, 1,000 of which must be contiguous — required during installation procedure

These block counts refer to the disk space required on the system disk. The sizes are approximate; actual sizes may vary depending on the user's system environment, configuration and software options selected.

- Extended Instruction Set (EIS)
- A device capable of reading one of the available distribution media

OPTIONAL HARDWARE

Supports any mass storage, printer, or terminal device supported by RT-11, with the additions of:

- KE11-B Instruction Set
- FP11 Floating Point Unit
- KEV11 Floating Point Instruction Set

HARDWARE NOT SUPPORTED

The Fixed Instruction Set (FIS) is not supported. The processors affected by this are:

- LSI-11
- LSI-11/2
- LSI-11/03
- PDP-11/40
- PDP-11/35

SOFTWARE REQUIREMENTS

RT-11 Operating System

Note: Please refer to the RT-11 SPD 12.01.xx for Run-Time System Licensing information that pertains to the execution of PDP-11 C images under a subset of the RT-11 Operating System.

Refer to the RT-11 Software Product Description (SPD 12.01.xx) for the required version.

OPTIONAL SOFTWARE

None

GROWTH CONSIDERATIONS

The minimum hardware requirements for any future version of this product may be different from the hardware requirements for the current version.

MEDIA DISTRIBUTION

The distribution Media Codes are described below. Specify the desired Media Code at the end of the Order Number, e.g., Qxxxx-H5 = binaries on TK50 Tape Cartridge.

5 = TK50 Tape Cartridge

M = 9-track 1600 BPI Magtape (PE)

Z = No hardware dependency

ORDERING INFORMATION*License Options:*

For Class L Systems¹

Single-Use License: QYV68-UZ

For Class L Systems²

Single-Use License: QJV68-UZ

Media and Service Options:

Software Media/Documentation: QJV68-H*

Software Documentation: QJV66-GZ

Software Product Services: QJV68-**

* Denotes variant fields. For additional information on available licenses, service, and media, refer to the appropriate price book.

Note: The availability of these software product options and services may vary by country. Customers should contact their local Digital office for information on availability.

¹ Class L Systems(low-end systems):

- All Q-bus models and systems
- KD11, KDF11, KDJ11 CPU modules
- DCT11, DCF11, DCJ11 microprocessor chips

² Class H Systems(high-end systems):

- All UNIBUS models and systems

SOFTWARE LICENSING

This software is furnished under the licensing provisions of Digital Equipment Corporation's Standard Terms and Conditions. For more information about Digital's licensing terms and policies, contact your local Digital office.

Note: The software being licensed is warranted only if the hardware configuration on which the software is run is a configuration explicitly supported by the RT-11 mapped Operating Systems (see SPD 12.01.xx).

Please refer to RT-11 (SPD 12.01.xx) for Run-Time licensing information. This may pertain to the execution of PDP-11 C images under some subset of the RT-11 Operating System.

SOFTWARE PRODUCT SERVICES

A variety of service options are available from Digital. For more information, contact your local Digital office.

SOFTWARE WARRANTY

Warranty for this software product is provided by Digital with the purchase of a license for the product as defined in the Software Warranty Addendum of this SPD.

TM The DIGITAL Logo, DEC, KD11, Q-bus, PDP-11 C, MicroRSX, RL, RSTS/E, RSX, RSX-11M, RSX-11S, RSX-11M-PLUS, RT, RT-11, TK, UNIBUS, and VAX-11 RSX are trademarks of Digital Equipment Corporation.

