

MAY 1998

DIGITAL Server Rackmount

DIGITAL[™] Server Rackmounts provide space-saving, secure enclosures for networked servers. Capitalizing on the rackmount-ready design of all DIGITAL servers, the easy-tointegrate 85", 69", and 50" rack enclosures support up to eight DIGITAL servers. Flexible configuration choices simplify the integration of clustering and networking options.

FEATURES

- Ease of integration and installation reduces cost of ownership.
- High capacity, small footprint maximizes use of space and investment.
- Secure, commercial-quality design for safe mission-critical computing environments.
- Supports up to eight DIGITAL servers without chassis modification or conversion kits.
- Flexible rack configurations allow for ready-to-run solutions to meet computing needs.
- One-year, on-site, next-businessday warranty.

digital

Features

VERTICAL CAPACITY

- 42U or 85" for high-capacity installation (1U = 1.75")
- 33U or 69" for medium capacity 22U or 50" for compact capacity

SECURITY

- · Locking front and rear doors
- Optional side panel locks

COOLING

- Six fans for maximum airflow and
- optimal cooling (42U and 33U) Vented front and rear doors

CONSOLE

- Four- or eight-port console
- · Desktop, rackmount or remote option

CABLING

- Cable management harnesses included
- Extension cables for remote management
- Retractable cable arms mounted on shelves

Configurations

DIGITAL[™] Server 19" RETMA Standard

- 42U, rack enclosure, 85" high, 115V 42U, rack enclosure, 85" high, 230V Rack with side panels includes: 12-14U mounting angles preinstalled and segmented, fan tray with cord, 20 bracing posts, cable ties, cable management rings, 6 fans, front stabilizer, front and rear doors, and side panels.
- 33U, rack enclosure, 69" high, 115V 33U, rack enclosure, 69" high, 230V Rack with side panels includes: 12-11U mounting angles preinstalled and segmented, fan tray with cord, 20 bracing posts, cable ties, cable management rings, 6 fans, front stabilizer, front
- and rear doors, and side panels. 22U, rack enclosure, 50" high, no fan Rack with side panels includes: 8-11U mounting angles preinstalled and segmented, fan tray (without fans), 20 bracing posts, cable ties, cable management rings, front stabilizer, front

and rear doors, and side panels.

Options

Shelves

Fixed monitor shelf (for FR-PCSRA-RC) Keyboard/mouse shelf (for FR-PCSRA-RC) Universal shelf for all DIGITAL servers (except DIGITAL Server 3105R, 3200R, 3205R, 3300R, 7100R, 7105R) keyboard, console, and monitor Split sliding shelf (for DIGITAL Server 3100/3200) Mouse shelf adds to universal shelf for mouse

Mounting Kits

DIGITAL Server 1200 Mounting Kit DIGITAL Server 5100 and 7100 Mounting Kit Chassis support rails for support of mounted 19" options, 2 per kit BA356 Mounting Kit RA310 Mounting Kit

For more information about DIGITAL products for Windows NT,

call 1-800-722-9332 or visit us at www.windows.digital.com

© Digital Equipment Corporation, 1998, DIGITAL, the DIGITAL logo, and ServerWORKS are trademarks of Digital Optime Equipment Corporation, 1996. District, the District tagg and Sarve works are adventions.
 Equipment Corporation, DIGTAL believes the information in this publication is accurate as of its publication date, such information is subject to change without notice. DIGTAL is not responsible for any inadvertent errors. DIGTAL conducts its business in a manner that conserves the environment and protects the safety and health of its employees, customers and the community.

Printed in the U.S.A. EC-F9199-88 Rel. #xx/98 xx xx 5.0 Copyright 1998 Digital Equipment Corporation. All rights reserved.

SIDE PANELS

Two removable side panels for baying

FRONT DOOR

Swing-out, locking door

Safety glass, high-quality finish

Vented for cooling

REAR DOOR

- Vented for cooling
- · Locks for added security

STABILIZER

•	Reliaciable for salely
•	Ensures steadiness during servicing

DIMENSIONS	42U	33U	22U
 Height: 	85.25"	69.25"	50.00"
Width:	23.75"	23.75"	23.75"
 Depth: 	35.50"	35.50"	35.50"
 Weight: 	396 lb	396 lb	396 lb

WARRANTY

· One-year, on-site, next-business-day response



42U enclosure shown with clustered DIGITAL Servers

Options (continued)

Accessories

15U blanking panel kit (1U, 2U, 4U, 8U panels) Side panel locks (4 locks per kit) Rack baying kit Guardian Virtual keyboard/mouse DIGITAL server power cord kit (8 cords) Fan assembly (22U), 115V Fan assembly (22U), 220V

Optional Assembly Consoles

Four-port desktop console (Multiplexes four servers into one desktop console) Eight-port desktop console (Multiplexes eight servers into one desktop console) Rackmounting Kit for four-port console Rackmounting Kit for eight-port console

Cables

- 10' cable for connecting two servers to console 20' cable for connecting two servers to console
- 25' extension cable allows for 20' remote operation
- of keyboard/monitor/mouse
- 3' cable for daisy chaining consoles
- 50' master console remote system for remote console operation 50' from the rack
- 100' master console remote system
- for remote console operation 100' from the rack 150' master console remote system
- for remote console operation 150' from the rack



DIGITAL Server Rackmount